



L10762

Resonant cavity LED for POF data communication

The L10762 is a red LED designed for POF data communications. A microball lens is bonded to the LED chip to enhance fibre-coupling efficiency.

Features

- **Improved fiber-coupling efficiency**
A microball lens is bonded to the LED chip surface to enhance the coupling efficiency to optical fibers. Fiber end output power ^{*2} was boosted about 7 times higher than our conventional type.
- **High-speed response: 70 MHz**

Applications

- **POF (plastic optical fiber) data communication**

Absolute maximum ratings

Parameter	Symbol	Value	Unit
Reverse voltage	V _R	3	V
Forward current	I _F	50	mA
Pulsed forward current ^{*1}	I _{FP}	80	mA
Operating temperature	T _{opr}	-30 to +85	°C
Storage temperature	T _{stg}	-40 to +100	°C

*1: Pulse width: 1 μs, Duty ratio=50 %


Electrical and optical characteristics (T_a=25 °C)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Peak emission wavelength	λ _p	I _F =20 mA	640	660	670	nm
Spectral half width	Δλ	I _F =20 mA	-	10	20	nm
Fiber end output ^{*2}	P _f	I _F =20 mA	0.7	1.0	-	mW
Forward voltage	V _F	I _F =20 mA	-	1.9	2.4	V
Reverse current	I _R	V _R =3 V	-	-	10	μA
Cut-off frequency ^{*3}	f _c	I _F =20 mA ±1 mAp-p	60	70	-	MHz

*2: Plastic fiber: 1 mm in core diameter, 1 meter in length, and Z (distance between cap surface and fiber end)=0.3 mm


*3: Frequency at which the radiant output drops by 3 dB relative to the output at 100 kHz

Emission spectrum




KLEDB0264EA

Fiber end output vs. forward current




KLEDB0331EA

Forward current vs. forward voltage




KLEDB0267EA

Fiber end output vs. ambient temperature




KLEDB0330EA

Allowable forward current vs. ambient temperature



KLEDB0027EB


Frequency characteristic



KLEDB0318EA


Fiber coupling characteristics

X, Y directions





KLEDB0313EA

Z direction



KLEDB0314EA

Dimensional outline (unit: mm)



Common to case



KLEDA0089EA

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions.

Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein.

Type numbers of products listed in the specification sheets or supplied as samples may have a suffix "(X)" which means tentative specifications or a suffix "(Z)" which means developmental specifications. ©2009 Hamamatsu Photonics K.K.

HAMAMATSU

www.hamamatsu.com

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 8152-375-0, Fax: (49) 8152-265-8

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741