

Spectroscopic modules



C15712

C15713

C15714

Compact module with MEMS-FPI spectrum sensor and light source

This compact module has a built-in light source, control circuit, and MEMS-FPI spectrum sensor consisting of an InGaAs PIN photodiode and MEMS-FPI (Fabry-Perot Interferometer) tunable filter which can vary its transmission wavelength by changing the applied voltage. Spectrum and absorbance can be measured by connecting a PC via USB. The product includes evaluation software with functions for setting measurement conditions, acquiring and saving data, drawing graphs, and so on. Furthermore, the dynamic link library (DLL) function specifications are disclosed, so users can create their original measurement software programs.

Features

- Compact, thin case
- MEMS-FPI spectrum sensor and light source are installed.
- Spectral response range
C15712: 1350 to 1650 nm
C15713: 1550 to 1850 nm
C15714: 1750 to 2150 nm
- External power supply not necessary: USB 2.0 bus powered
- Transmission wavelength shift due to the ambient temperature change is corrected.
- High-speed measurement

Applications

- Moisture detection
- Food inspection
- Farm product inspection
- Plastic screening
- Fabric identification, etc.

Structure

Parameter	C15712	C15713	C15714	Unit
Sensor	C14272	MEMS-FPI spectrum sensor C13272-03		-
Light source	Tungsten lamp			-
Interface	USB 2.0 micro-B			-
Dimensions	74 × 32 × 16			mm
Weight	82			g

Absolute maximum ratings

Parameter	Symbol	Value	Unit
Operating temperature*1	Topr	-5 to +50	°C
Storage temperature*1	Tstg	-20 to +70	°C

*1: No dew condensation

When there is a temperature difference between a product and the surrounding area in high humidity environments, dew condensation may occur on the product surface. Dew condensation on the product may cause deterioration in characteristics and reliability.

Note: Exceeding the absolute maximum ratings even momentarily may cause a drop in product quality. Always be sure to use the product within the absolute maximum ratings.

Optical characteristics (Ta=25 °C unless otherwise noted)

Parameter	Symbol	C15712			C15713			C15714			Unit
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	
Spectral response range*2	λ	1350	-	1650	1550	-	1850	1750	-	2150	nm
Spectral resolution (FWHM)*3	-	-	-	18	-	-	20	-	-	22	nm
Wavelength reproducibility*4	λ_r	-	± 2	-	-	± 2	-	-	± 2	-	nm
Wavelength temperature dependence*5	λT_d	-0.1	-	+0.1	-0.1	-	+0.1	-0.1	-	+0.1	nm/°C

*2: Minimum step 0.1 nm, maximum 901 wavelength points can be set.

*3: When the light [line spectrum resolution (FWHM)=3 nm max.] is input from the optical fiber (core diameter=600 μ m, NA=0.22) connected by the fiber adapter A15719.

*4: When the incident light condition and usage environment are constant


*5: Topr=-5 to +50 °C, C15712: λ =1500 nm, C15713: λ =1700 nm, C15714: λ =1950 nm

Electrical characteristics (Ta=25 °C unless otherwise noted)

Parameter	Specification	Unit
A/D conversion	16	bit
Gain*6	Low	1.05×10^6
	Middle	1.05×10^7
	High	2.23×10^7
USB bus power current consumption	Typ.	350
	Max.	450
		mA

*6: Design value


Spectral resolution vs. peak transmission wavelength (typical example)



KACCB0624EA


Spectral response (typical example)

C15712




KACCB0625EA

C15713



KACCB0626EA

C15714



KACC0627EA

❏ Evaluation software (accessory)

By installing the evaluation software (FPIModuleEvaluation.exe) into a PC, you can perform the following basic operations.

- Acquire, save measurement data
- Set measurement conditions
- Set built-in lamp
- Acquire module information (type number, serial number, spectral response range, etc.)
- Display graphs
- Calculation functions
Comparison with the reference data (reflectance, absorbance, etc.)

Note: Up to eight spectroscopic modules can be connected to a single PC and used.

Compatible OS: Microsoft® Windows® 10 (32-bit, 64-bit)


A DLL for controlling the hardware is available.

The DLL and sample software is created in the following development environment, so users can develop original measurement programs.

DLL: Microsoft Visual Studio® 2017 Visual C++®

Sample software: Microsoft Visual Studio 2017 Visual C#®


Note: Microsoft, Windows, Visual Studio, Visual C++, and Visual C# are registered trademarks of Microsoft Corporation in the United States and/or other countries.



Connection examples

Reflected light measurement


Place cloth, plastic, etc. on the window material of the spectroscopic module connected to a PC via USB. The light from the light source built into the spectroscopic module strikes the object, and the spectroscopic module measures the reflected light.



KACCC1033EA


Transmitted light measurement

When measuring transmitted light, a light source must be prepared (the light source built into the spectroscopic module cannot be used).




KACCC1034EA

Measurement example (cloth)



KACCB0628EA

Dimensional outline (unit: mm)



KACCA0453EA

Accessories

- CD-ROM (instruction manual, evaluation software, sample software, DLL, etc.)
- USB cable (USB 2.0 micro-B connector type)

Precautions

This product has a built-in high-voltage power supply. To avoid danger, do not disassemble.

Options (sold separately)

Optical fiber adapter A15719

This is an adapter for simply coupling an optical fiber with an SMA connector to the spectroscopic module (C15712, C15713, C15714). Fix it to the spectroscopic module using the screw (included).

Note: The optical fiber is not included.

Optical components such as a condenser lens are not installed.



Related information

www.hamamatsu.com/sp/ssd/doc_en.html

- Precautions
- Disclaimer

- Technical information
- MEMS-FPI spectrum sensors, spectroscopic modules

Information described in this material is current as of July 2020.

Product specifications are subject to change without prior notice due to improvements or other reasons. This document has been carefully prepared and the information contained is believed to be accurate. In rare cases, however, there may be inaccuracies such as text errors. Before using these products, always contact us for the delivery specification sheet to check the latest specifications.

The product warranty is valid for one year after delivery and is limited to product repair or replacement for defects discovered and reported to us within that one year period. However, even if within the warranty period we accept absolutely no liability for any loss caused by natural disasters or improper product use. Copying or reprinting the contents described in this material in whole or in part is prohibited without our prior permission.

HAMAMATSU

www.hamamatsu.com

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81)53-434-3311, Fax: (81)53-434-5184

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, Bridgewater, N.J. 08807, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218, E-mail: usa@hamamatsu.com

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-265-8, E-mail: info@hamamatsu.de

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10, E-mail: infos@hamamatsu.fr

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, UK, Telephone: (44)1707-294888, Fax: (44)1707-325777, E-mail: info@hamamatsu.co.uk

North Europe: Hamamatsu Photonics Norden AB: Torshamnsgatan 35 16440 Kista, Sweden, Telephone: (46)8-509 031 00, Fax: (46)8-509 031 01, E-mail: info@hamamatsu.se

Italy: Hamamatsu Photonics Italia S.r.l.: Strada della Moia, 1 int. 6, 20020 Arese (Milano), Italy, Telephone: (39)02-93 58 17 33, Fax: (39)02-93 58 17 41, E-mail: info@hamamatsu.it

China: Hamamatsu Photonics (China) Co., Ltd.: 1201 Tower B, Jiaming Center, 27 Dongsanhuan Beilu, Chaoyang District, 100020 Beijing, P.R.China, Telephone: (86)10-6586-6006, Fax: (86)10-6586-2866, E-mail: hpc@hamamatsu.com.cn

Taiwan: Hamamatsu Photonics Taiwan Co., Ltd.: 8F-3, No. 158, Section2, Gongdao 5th Road, East District, Hsinchu, 300, Taiwan R.O.C. Telephone: (886)3-659-0080, Fax: (886)3-659-0081, E-mail: info@hamamatsu.com.tw