



# Si Photodiodes


Lineup of Si photodiodes for UV to near IR, radiation



■ Ceramic package Si photodiode  
S12915 -33R



■ 16-element Si photodiode array  
S12859-021



■ Surface mount type Si PIN photodiode  
S15193

*Si Photodiodes*




# Si Photodiodes

Lineup of Si photodiodes for UV to near IR, radiation



# Contents

■ Packages	5
■ Application examples	8
■ Si photodiodes for precision photometry	9
• For UV to near IR	9
• For UV to near IR (IR sensitivity suppressed type)	11
• For UV monitor	12
• For visible range to near IR	13
■ Si photodiodes for general photometry/visible range	15
• For visible range	15
• For visible range to near IR	16
■ High-speed response Si PIN photodiodes	17
• Cutoff frequency: 1 GHz or more	17
• Cutoff frequency: 100 MHz to less than 1 GHz	18
• Cutoff frequency: 10 MHz to less than 100 MHz	19
■ Multi-element type Si photodiodes	21
• Segmented type Si PIN photodiodes	21
• One-dimensional photodiode arrays (UV to near IR: UV sensitivity enhanced type)	22
■ Surface mount type Si photodiodes	23
• High-speed response Si PIN photodiodes	23
• Segmented type Si photodiodes	23
• Small package type Si photodiodes	24
• Small package type Si PIN photodiodes	25
■ Si photodiodes with preamp, TE-cooled type Si photodiodes	26
• Si photodiodes with preamp for measurement	26
• TE-cooled type Si photodiodes	27
■ Si photodiodes for X-ray detection	28
• Si photodiodes with scintillator	28
• Large area Si PIN photodiodes	30
• Large area type Si PIN photodiodes for direct radiation detection	32
■ Special application Si photodiodes	33
• RGB color sensors	33
• Violet/blue sensitivity enhanced type	35
• For VUV (vacuum ultraviolet) monitor	36
• For VUV detection (high reliability type)	36
• For monochromatic light detection	37
• For YAG laser detection	37
• For electron beam detector	38
• PWB package with leads type	38
• CSP type	39
• CSP type 64-element Si photodiode array	39
• 6-element array for encoder	39
■ Related products of Si photodiode	40
• RGB color sensor modules	40
• Color sensor evaluation circuit	40
• Driver circuit for Si photodiode array	41
• Photodiode modules	41
• Signal processing unit for photodiode module	41
• Photosensor amplifier	42
• Charge amplifier	43
■ Description of terms	44



# Si photodiodes

Photodiodes are semiconductor light sensors that generate a current or voltage when the P-N junction in the semiconductor is illuminated by light. The term photodiode can be broadly defined to include even solar batteries, but it usually refers to sensors used to detect the intensity of light. Photodiodes can be classified by function and construction as follows:

- Si photodiode
- Si PIN photodiode
- Si APD (avalanche photodiode)

All of these types provide the following features and are widely used for the detection of the presence, intensity and color of light.

- Excellent linearity with respect to incident light
- Low noise
- Wide spectral response range
- Mechanically rugged
- Compact and lightweight
- Long life

Si photodiodes manufactured utilizing our unique semiconductor process technologies cover a broad spectral range from the near infrared to ultraviolet and even to high-energy regions. They also feature high-speed response, high sensitivity and low noise. Si photodiodes are used in a wide range of applications including medical and analytical fields, scientific measurements, optical communications and general electronic products. Si photodiodes are available in various packages such as metal, ceramic and plastic packages as well as in surface mount types. We also offer custom-designed devices to meet special needs.

## ◆ Hamamatsu Si photodiodes

Type	Feature	Product example
Si photodiode	Featuring high sensitivity and low dark current, these Si photodiodes are specifically designed for precision photometry and general photometry/visible range.	<ul style="list-style-type: none"> <li>• For UV to near IR</li> <li>• For visible range to near IR</li> <li>• For visible range</li> <li>• RGB color sensor</li> <li>• For monochromatic light detection</li> <li>• For VUV (vacuum ultraviolet) detection</li> <li>• For electron beam detector</li> </ul>
Si PIN photodiode	Si PIN photodiodes delivering high-speed response when operated with a reverse bias are widely used for optical communications and optical disk pickup, etc.	<ul style="list-style-type: none"> <li>• Cutoff frequency: 1 GHz or more</li> <li>• Cutoff frequency: 100 MHz to less than 1 GHz</li> <li>• Cutoff frequency: 10 MHz to less than 100 MHz</li> <li>• For YAG laser detection</li> </ul>
Multi-element type Si photodiode	Si photodiode arrays consist of multiple elements of the same size, formed at an equal spacing in one package. These Si photodiode arrays are used in a wide range of applications such as laser beam position detection and spectrophotometry.	<ul style="list-style-type: none"> <li>• Segment type</li> <li>• One-dimensional type</li> </ul>
Si photodiode with preamp, TE-cooled type Si photodiode	Si photodiodes with preamp incorporate a photodiode and a pre-amplifier chip into the same package. Since TE-cooled type Si photodiodes include TE-cooler in a package, they achieve excellent S/N.	<ul style="list-style-type: none"> <li>• For analytical and measurement instrument</li> </ul>
Si photodiode for X-ray detection	These detectors are comprised of a Si photodiode coupled to a scintillator. These detectors are used for X-ray baggage inspection and non-destructive inspection.	<ul style="list-style-type: none"> <li>• With scintillator</li> <li>• Large area Si PIN photodiodes</li> </ul>
Si APD*	Si APDs are high-speed, high sensitivity photodiodes having an internal gain mechanism.	<ul style="list-style-type: none"> <li>• Near IR type</li> <li>• Short wavelength type</li> <li>• Multi-element type</li> </ul>
Related product of Si photodiode	Hamamatsu provides various types of Si photodiode modules.	<ul style="list-style-type: none"> <li>• RGB color sensor module</li> <li>• Color sensor evaluation circuit</li> <li>• Driver circuit for Si photodiode array</li> <li>• Photodiode module</li> <li>• Signal processing unit for photodiode module</li> <li>• Photosensor amplifier</li> <li>• Charge amplifier</li> </ul>


\* Si APD is not listed in this catalogue.

Note: Hamamatsu also provides PSD (position sensitive detector) used to detect the position of incident light spot. PSD is a non-discrete photosensor utilizing the surface resistance of photodiodes.

**Spectral response (typical example)**


Hamamatsu provides a lineup that covers a variety of spectral response ranges from 200 nm to 1200 nm.

[ S1226/S1336-8BQ, S1227/S1337-1010BR ]



KSPDB0300EC

[ S3590-19, S9219 ]



KSPDB0301EC

# Packages

Hamamatsu provides a wide variety of packages including metal, ceramic, and plastic.

## ◆ Si photodiodes for precision photometry

Type	Type no.	Page	Metal	Ceramic	Plastic	Glass epoxy	With BNC connector	Remarks
For UV to near IR	S1336 series	9	Yes					
	S1337 series (excluding S1337-21)	9		Yes				
	S1337-21	10		Yes				Unsealed
	S2551	10		Yes				
	S2281 series	10					Yes	
For UV to near IR (IR sensitivity suppressed type)	S1226 series	11	Yes					
	S1227 series	11		Yes				
	S2281-01	11					Yes	
For UV monitor	S12698 series	12	Yes					
For visible range to near IR	S2386 series	13	Yes					
	S12915 series	14		Yes				

## ◆ Si photodiodes for general photometry/visible range

Type	Type no.	Page	Metal	Ceramic	Plastic	Glass epoxy	With BNC connector	Remarks
For visible range	Visual-sensitive compensated	S1087, S1133, S8265	15			Yes		
		S1787-04	15		Yes			
	CIE standard luminous efficiency approximation	S9219	15					Yes
		S9219-01	15	Yes				
		S7686	15		Yes			
For visible range to near IR	S1787-12, S4797-01 S4011-06DS S1787-08, S2833-01	16			Yes			
	S1133-14, S1087-01 S1133-01	16		Yes				

## ◆ High-speed response Si PIN photodiodes

Type	Type no.	Page	Metal	Ceramic	Plastic	Glass epoxy	With BNC connector	Remarks
Cutoff frequency: 1 GHz or more	S5973/S9055 series	17	Yes					
Cutoff frequency: 100 MHz to less than 1 GHz	S5971, S3399 S3883, S5972	18	Yes					
	S10783, S10784	18			Yes			
Cutoff frequency: 10 MHz to less than 100 MHz	S6775/S8729/ S2506 series S6967, S8385 S4707-01, S6801-01	19			Yes			
	S5821/S1223 series S3071, S3072 S12271	20	Yes					

## ◆ Multi-element type Si photodiodes

Type	Type no.	Page	Metal	Ceramic	Plastic	Glass epoxy	With BNC connector	Remarks
Segmented type Si PIN photodiode	S3096-02, S4204, S9345	21			Yes			
	S4349	21	Yes					
One-dimensional photodiode array	S4111/S4114 series	22		Yes				
	S12858/S12859/ S11212/S11299/ S12362/S12363-021	22				Yes		Unsealed

### ◆ Surface mount type Si photodiodes

Type	Type no.	Page	Metal	Ceramic	Plastic	Glass epoxy	With BNC connector	Remarks
High-speed response Si PIN photodiode	S5106, S5107 S7509, S7510	23		Yes				Surface mount type
Segmented type Si photodiode	S5980, S5981, S5870 S8558, S15158	23		Yes		Yes		Surface mount type
Small package type Si photodiode	S9674, S9981-01CT S10625-01CT	24				Yes		Surface mount type
Small package type Si PIN photodiode	S13773 S10993-02CT, S12158-01CT S13954-01CT, S14016-01DT	25				Yes		Surface mount type

### ◆ Si photodiodes with preamp, TE-cooled type Si photodiodes

Type	Type no.	Page	Metal	Ceramic	Plastic	Glass epoxy	With BNC connector	Remarks
Si photodiode with preamp for measurement	S8745-01, S8746-01 S9295 series	26	Yes					
TE-cooled type Si photodiode	S2592/S3477 series	27	Yes					

### ◆ Si photodiodes for X-ray detection

Type	Type no.	Page	Metal	Ceramic	Plastic	Glass epoxy	With BNC connector	Remarks
Si photodiode with scintillator	S8559, S8193	28		Yes				With scintillator
	S12858/S12859/ S11299/S11212/ S12362/S12363 series	28				Yes		With scintillator
Large area type Si PIN photodiode	S3590 series S8650	30		Yes				
	S2744/S3204/ S3584/S3588 series	31		Yes				
Large area type Si PIN photodiodes for direct radiation detection	S13993, S14605	32		Yes				Unsealed

### ◆ Special application Si photodiodes

Type	Type no.	Page	Metal	Ceramic	Plastic	Glass epoxy	With BNC connector	Remarks
RGB color sensor	S7505-01, S9032-02 S9702	33			Yes			Surface mount type
	S10917-35GT S10942-01CT	33				Yes		Surface mount type
	S6428-01, S6429-01 S6430-01	34			Yes			
Violet/blue sensitivity enhanced type	S5973-02, S9195	35	Yes					
	S3994-01	35		Yes				
For VUV (vacuum ultraviolet) monitor	S8552, S8553	36		Yes				Unsealed
For VUV detection (high reliability type)	S10043	36		Yes				Unsealed
For monochromatic light detection	S12742 series	37	Yes					
For YAG laser detection	S3759	37	Yes					
For electron beam detector	S11141 series	38		Yes				Unsealed
PWB package with leads type	S12497, S12498	38				Yes		Unsealed
CSP type	S13955-01, S13956-01 S13957-01	39				Yes		Unsealed
CSP type 64-element Si photodiode array	S13620-02	39				Yes		Unsealed
6-element array for encoder	S14833	39				Yes		Surface mount type

## Variety of package types

Hamamatsu offers a diverse selection of package types to meet different customer needs. Metal packages are widely used in applications requiring high reliability. Ceramic packages are used for general applications and plastic packages are used in applications where the main need is low cost.

Other types are also available including those with BNC connector, which facilitates connection to coaxial cable, surface mount types that support reflow soldering, and those with scintillator, which converts X-rays and radiation to visible light.



## Mount technology

At the Solid State Division of Hamamatsu Photonics, we are constantly at work designing and developing our own mount technology to offer unique semiconductor devices having special features.

Now we will take a brief look at our mount technology for Si photodiodes.

### ▲ Flip chip bonding

Mounting technology for opto-semiconductors includes not only the two-stage chip die-bonding and wire-bonding but also the flip chip bonding as shown in Figure 1.

Parasitic capacitance and inductance can be a problem when extracting opto-semiconductor device signals from a wire. Flip-chip bonding can prevent this problem and help in downsizing since it utilizes bumps to directly join the chip to the package or an IC chip, etc.

### ▲ CSP (chip size package)

In CSP type photodiodes, the chip and substrate are connected by bump electrodes so there is minimal dead area on the package surface area. This allows utilizing the photosensitive area more effectively. Also multiple devices can be densely arrayed and used in a tile format. There is no wiring so coupling to the scintillator is easy.

Figure 1 Example of flip chip bonding





Figure 2 Cross section of CSP type photodiode




KSPDC0065EB



# Application examples


Here, we will introduce several applications of our Si photodiodes.

## Optical power meters




Large area type Si PIN photodiodes are used to measure the light levels of various light sources such as laser diodes and LEDs.

## LCD backlight color adjustment




The RGB color sensor detects the white balance of LCD backlight optical waveguides and controls the light level of each RGB LED to stabilize the LCD backlight color.

## Sunlight sensors



Si photodiodes are used to detect the amount of sunshine to control the volume of air flow for automotive air conditioners.

## Spectrophotometers




Si photodiode arrays are used to detect light that has been divided into wavelengths through a diffraction grating in spectrophotometers.

## Radiation detectors



Si PIN photodiodes with scintillators are used in detectors that measure radiation levels of  $\gamma$  rays and other rays.

## Baggage inspection equipment









Si PIN photodiodes with scintillators are used in dual energy imaging of baggage inspection equipment to obtain information about an object such as its type and thickness.

# Si photodiodes for precision photometry

For UV to near IR


These Si photodiodes have sensitivity in the UV to near IR range. They are suitable for low-light-level detection in analysis and the like. (Typ. Ta=25 °C)

Type no.	Spectral response range (nm)	Photosensitivity (A/W)		Dark current VR=10 mV max. (pA)	Terminal capacitance VR=0 V f=10 kHz (pF)	Photosensitive area size (mm)	Package	Photo			
		λ=200 nm	λ=960 nm								
S1336-18BQ*1	190 to 1100	0.12	0.5	20	20	1.1 × 1.1	TO-18				
S1336-18BK	320 to 1100	-		30	65	2.4 × 2.4	TO-5				
S1336-5BQ*1	190 to 1100	0.12									
S1336-5BK	320 to 1100	-									
S1336-44BQ*1	190 to 1100	0.12									
S1336-44BK	320 to 1100	-									
S1336-8BQ*1	190 to 1100	0.12							100	380	5.8 × 5.8
S1336-8BK	320 to 1100	-	50	65	1.1 × 5.9	Ceramic					
S1337-16BQ*1	190 to 1100	0.12						0.5			
S1337-16BR	340 to 1100	-			0.62						
S1337-33BQ*1	190 to 1100	0.12			0.5			30	2.4 × 2.4		
S1337-33BR	340 to 1100	-			0.62						
S1337-66BQ*1	190 to 1100	0.12			0.5			100	5.8 × 5.8		
S1337-66BR	340 to 1100	-			0.62						
S1337-1010BQ*1	190 to 1100	0.12			0.5			200	1100	10 × 10	
S1337-1010BR	340 to 1100	-			0.62						


\*1: Refer to "Precautions against UV light exposure" (P.45).

## Spectral response

[ S1336-BQ, S1337-BQ ]




[ S1336-BK, S1337-BR ]




## Dark current vs. reverse voltage




[ S1336 series ]



[ S1337 series ]



(Typ. Ta=25 °C)


Type no.	Spectral response range (nm)	Photosensitivity (A/W)		Dark current VR=10 mV max. (pA)	Terminal capacitance VR=0 V f=10 kHz (pF)	Photosensitive area size (mm)	Package	Photo
		$\lambda=200$ nm	$\lambda=960$ nm					
S1337-21*2	190 to 1100	0.13	0.52	500	4000	18 × 18	Ceramic (unsealed)	
S2551	340 to 1060	-	0.57 ( $\lambda=920$ nm)	1000	350	1.2 × 29.1	Ceramic	
S2281*2 *3	190 to 1100	0.12	0.5	500	1300	$\phi 11.3$	With BNC connector	
S2281-04*2 *3								$\phi 7.98$

\*2: Refer to "Precautions against UV light exposure" (P.45).

\*3: Connecting a photodiode to the C9329 photosensor amplifier (using a BNC-BNC coaxial cable E2573) allows amplifying the photodiode's weak photocurrent with low noise.


## Spectral response

[ S1337-21 ]




KSPDB0304EA

[ S2551 ]



KSPDB0173EB


[ S2281, S2281-04 ]



KSPDB0270EA


## Dark current vs. reverse voltage

[ S1337-21 ]




KSPDB0305EA

[ S2551 ]



KSPDB0175EB

[ S2281, S2281-04 ]












KSPDB0271EB

## For UV to near IR (IR sensitivity suppressed type)




These Si photodiodes have suppressed IR sensitivity. They are suitable for low-light-level detection in analysis and the like.

(Typ. Ta=25 °C)




Type no.	Spectral response range (nm)	Photosensitivity (A/W)		Dark current VR=10 mV max. (pA)	Terminal capacitance VR=0 V f=10 kHz (pF)	Photosensitive area size (mm)	Package	Photo
		$\lambda=200$ nm	$\lambda=720$ nm					
S1226-18BQ*1	190 to 1000	0.12	0.36	2	35	1.1 × 1.1	TO-18	
S1226-18BK	320 to 1000	-						
S1226-5BQ*1	190 to 1000	0.12		5	160	2.4 × 2.4	TO-5	
S1226-5BK	320 to 1000	-						
S1226-44BQ*1	190 to 1000	0.12		10	500	3.6 × 3.6	TO-5	
S1226-44BK	320 to 1000	-						
S1226-8BQ*1	190 to 1000	0.12		20	1200	5.8 × 5.8	TO-8	
S1226-8BK	320 to 1000	-						
S1227-16BQ*1	190 to 1000	0.12	5	170	1.1 × 5.9	Ceramic		
S1227-16BR	340 to 1000	-						
S1227-33BQ*1	190 to 1000	0.12	20	950	5.8 × 5.8	Ceramic		
S1227-33BR	340 to 1000	-						
S1227-66BQ*1	190 to 1000	0.12	50	3000	10 × 10	Ceramic		
S1227-66BR	340 to 1000	-						
S1227-1010BQ*1	190 to 1000	0.12	50	3000	10 × 10	Ceramic		
S1227-1010BR	340 to 1000	-						
S2281-01*1	190 to 1000	0.12	0.36	300	3200	$\phi 11.3$	With BNC connector	

\*1: Refer to "Precautions against UV light exposure" (P.45).

## Spectral response






## Dark current vs. reverse voltage




For UV monitor

The S12698 series are Si photodiodes that have achieved high reliability for monitoring ultraviolet light by employing a structure that does not use resin. They exhibit low sensitivity deterioration under UV light irradiation and are suitable for applications such as monitoring intense UV light sources. (Typ. Ta=25 °C)

Type no.	Photosensitivity $\lambda=\lambda_p$ (A/W)	Dark current $V_R=10\text{ mV}$ max. (pA)	Photosensitive area size (mm)	Package	Photo
S12698*2	0.38	10	1.1 × 1.1	TO-18	
S12698-01*2		30	2.4 × 2.4	TO-5	
<b>NEW</b> S12698-04*2		50	3.6 × 3.6		
S12698-02*2		100	5.8 × 5.8	TO-8	


\*2: Refer to "Precautions against UV light exposure ①" (P.45).

Spectral response



KSPDB0350EB

Changes in spectral response after irradiated with UV light






KSPDB0355EA


## For visible range to near IR

These Si photodiodes offer enhanced sensitivity especially in the near IR range.

(Typ.  $T_a=25\text{ }^\circ\text{C}$ )


Type no.	Spectral response range (nm)	Photosensitivity $\lambda=960\text{ nm}$ (A/W)	Dark current $V_R=10\text{ mV}$ max. (pA)	Terminal capacitance $V_R=0\text{ V}$ $f=10\text{ kHz}$ (pF)	Photosensitive area size (mm)	Package	Photo
S2386-18K	320 to 1100	0.6	2	140	$1.1 \times 1.1$	TO-18	
S2386-18L							
S2386-5K			5	730	$2.4 \times 2.4$	TO-5	
S2386-44K			20	1600	$3.6 \times 3.6$		
S2386-45K			30	2300	$3.9 \times 4.6$		
S2386-8K					50	4300	$5.8 \times 5.8$

### Spectral response







KSPDB0272EE

### Dark current vs. reverse voltage




KSPDB0113EE


(Typ. Ta=25 °C)

Type no.	Spectral response range (nm)	Photosensitivity $\lambda=960$ nm (A/W)	Dark current $V_R=10$ mV max. (pA)	Terminal capacitance $V_R=0$ V $f=10$ kHz (pF)	Photosensitive area size (mm)	Package	Photo
S12915-16R	340 to 1100	0.64	5	740	1.0 × 6.0	Ceramic	
S12915-33R				680	2.4 × 2.4		
S12915-66R			50	5.8 × 5.8			
S12915-1010R			200	13000	10 × 10		

**Spectral response**



**Dark current vs. reverse voltage**



# Si photodiodes for general photometry/visible range

## For visible range





These Si photodiodes have sensitivity in the visible range.

(Typ. Ta=25 °C)




Type no.	Spectral response range (nm)	Peak sensitivity wavelength (nm)	Photosensitivity $\lambda=\lambda_p$ (A/W)	Dark current $V_R=1\text{ V}$ max. (pA)	Photosensitive area size (mm)	Package	Photo
----------	------------------------------	----------------------------------	--	---	-------------------------------	---------	-------

## Filter type (general use)

These are Si photodiodes with visible-compensated filters. The S8265 is a high humidity resistance type of the S1133.


S1087	320 to 730	560	0.3	10	1.3 × 1.3	Ceramic	
S1133					2.4 × 2.8		
S8265	340 to 720	540		20	2.4 × 2.8	Ceramic	
S1787-04	320 to 730	560		10	2.4 × 2.8	Plastic	

## Filter type (CIE spectral luminous efficiency approximation)

S9219	380 to 780	550	0.24	500 ( $V_R=10\text{ mV}$ )	$\phi 11.3$	With BNC connector	
S9219-01			0.22	50 ( $V_R=10\text{ mV}$ )	3.6 × 3.6	TO-5	
S7686	480 to 660		0.38	20	2.4 × 2.8	Ceramic	


## Spectral response

[ S1087, S1133, S1787-04, S8265 ]



KSPD80277ED

[ S9219 series, S7686 ]



KSPD80285EE













## For visible range to near IR


These Si photodiodes have sensitivity in the visible range to near IR.

(Typ.  $T_a=25\text{ }^\circ\text{C}$ )


Type no.	Spectral response range (nm)	Peak sensitivity wavelength (nm)	Photosensitivity $\lambda=\lambda_p$ (A/W)	Dark current $V_R=1\text{ V max.}$ (pA)	Photosensitive area size (mm)	Package	Photo
S1787-12	320 to 1000	650	0.35	20	2.4 × 2.8	Plastic	
S4797-01		720	0.4		1.3 × 1.3		
S1133-14					Ceramic	2.4 × 2.8	
S4011-06DS	320 to 1100	960	0.58	10	1.3 × 1.3	Plastic	
S1787-08					2.4 × 2.8		
S2833-01					Ceramic		
S1087-01					1.3 × 1.3	Ceramic	
S1133-01					2.4 × 2.8		

## Spectral response

[ S1787-12, S4797-01, S1133-14 ]






[ S4011-06DS, S1787-08, S2833-01, S1087-01, S1133-01 ]




# High-speed response Si PIN photodiodes

Cutoff frequency: 1 GHz or more


These Si PIN photodiodes deliver a wide bandwidth even with a low bias, making them suitable for high-speed photometry as well as optical communications. (Typ.  $T_a=25\text{ }^\circ\text{C}$ )

Type no.	Cutoff frequency (GHz)	Photosensitive area size (mm)	Photosensitivity (A/W)		Terminal capacitance $f=1\text{ MHz}$ (pF)	Package	Photo
			$\lambda=780\text{ nm}$	$\lambda=830\text{ nm}$			
S5973	1 ( $V_R=3.3\text{ V}$ )	$\phi 0.4$	0.51	0.47	1.6 ( $V_R=3.3\text{ V}$ )	TO-18	
S5973-01							
S9055	1.5 ( $V_R=2\text{ V}$ )	$\phi 0.2$	0.35	0.25	0.8 ( $V_R=2\text{ V}$ )		
S9055-01	2 ( $V_R=2\text{ V}$ )						$\phi 0.1$

## Spectral response




## Terminal capacitance vs. reverse voltage




## Frequency response

[ S5973, S5973-01 ]




[ S9055 series ]

$\lambda=410\text{ nm}$








$\lambda=830\text{ nm}$



Cutoff frequency: 100 MHz to less than 1 GHz


These Si PIN photodiodes have a large photosensitive area ( $\phi 0.8$  to  $\phi 3$  mm) yet deliver excellent frequency response characteristics.

(Typ.  $T_a=25^\circ\text{C}$ )

Type no.	Cutoff frequency (MHz)	Photosensitive area size (mm)	Photosensitivity (A/W)		Terminal capacitance f=1 MHz (pF)	Package	Photo
			$\lambda=660$ nm	$\lambda=780$ nm			
S5971	100 ( $V_R=10$ V)	$\phi 1.2$	0.44	0.55	3 ( $V_R=10$ V)	TO-18	
S3399		$\phi 3$	0.45	0.58	20 ( $V_R=10$ V)		
S3883	300 ( $V_R=20$ V)	$\phi 1.5$			6 ( $V_R=20$ V)	TO-5	
S10783	300 ( $V_R=2.5$ V)	$\phi 0.8$	0.46	0.52	4.5 ( $V_R=2.5$ V)		Plastic
S10784		$\phi 3$	0.45	0.51		Plastic with lens	
S5972	500 ( $V_R=10$ V)	$\phi 0.8$	0.44	0.55	3 ( $V_R=10$ V)	TO-18	


Spectral response

[ S5971, S3399, S3883 ]




KPINB0316EC

[ S10783, S10784 ]



KPINB0355EC


[ S5972 ]



KPINB0315ED


Terminal capacitance vs. reverse voltage

[ S5971, S3399, S3883 ]




KPINB0341EC

[ S10783, S10784 ]



KPINB0358EC

[ S5972 ]













KPINB0338EB

## Cutoff frequency: 10 MHz to less than 100 MHz


A wide variety of types are provided including a low-cost plastic package type and visible-cut type.

(Typ. Ta=25 °C)

Type no.	Cutoff frequency (MHz)	Photosensitive area size (mm)	Photosensitivity (A/W)		Terminal capacitance f=1 MHz (pF)	Package	Photo
			$\lambda=660$ nm	$\lambda=780$ nm			
S6775	15 (VR=10 V)	5.5 × 4.8	0.45	0.55	40 (VR=10 V)	Plastic	
S6967	50 (VR=10 V)				50 (VR=10 V)		
S6775-01	15 (VR=10 V)		0.54 ( $\lambda=830$ nm)	0.68 ( $\lambda=\lambda_p$ )	40 (VR=10 V)		
S8385	25 (VR=5 V)	2 × 2	0.4	0.48	12 (VR=5 V)		
S8729		2 × 3.3	0.45	0.55	16 (VR=5 V)		
S8729-04			0.52 ( $\lambda=830$ nm)	0.68 ( $\lambda=\lambda_p$ )			
S8729-10			0.45	0.55			
S2506-02			2.77 × 2.77	0.4			0.48
S2506-04	0.25 ( $\lambda=830$ nm)	0.56 ( $\lambda=\lambda_p$ )					
S4707-01	20 (VR=10 V)	2.4 × 2.8	0.4	0.48	14 (VR=10 V)		
S6801-01	15 (VR=10 V)	$\phi 14$ (lens diameter)	0.52 ( $\lambda=830$ nm)	0.65 ( $\lambda=\lambda_p$ )	50 (VR=10 V)	Plastic with $\phi 14$ mm lens 	


## Spectral response

[ S8385/S8729 series ]




KPINB0324EF

[ S6775/S6967/S2506 series ]










KPINB0167EG

[ S4707-01, S6801-01 ]



KPINB0354EB


(Typ. Ta=25 °C)

Type no.	Cutoff frequency (MHz)	Photosensitive area size (mm)	Photosensitivity (A/W)		Terminal capacitance f=1 MHz (pF)	Package	Photo
			$\lambda=660$ nm	$\lambda=780$ nm			
S5821	25 (V <sub>R</sub> =10 V)	$\phi$ 1.2	0.45	0.52	3 (V <sub>R</sub> =10 V)	TO-18	
S5821-02							
S5821-01							
S5821-03							
S1223	30 (V <sub>R</sub> =20 V)	2.4 × 2.8	0.45	0.52	10 (V <sub>R</sub> =20 V)	TO-5	
S1223-01	20 (V <sub>R</sub> =20 V)	3.6 × 3.6					20 (V <sub>R</sub> =20 V)
S3072	45 (V <sub>R</sub> =24 V)	$\phi$ 3	0.47	0.54	7 (V <sub>R</sub> =24 V)	TO-8	
S3071	40 (V <sub>R</sub> =24 V)	$\phi$ 5					18 (V <sub>R</sub> =24 V)
S12271*	60 (V <sub>R</sub> =100 V)	$\phi$ 4.1	0.5 ( $\lambda=960$ nm)		10 (V <sub>R</sub> =100 V)		

\* Refer to "Precautions against UV light exposure" (P.45).


### Spectral response

[ S5821 series, S3071, S3072 ]




KPINB0335EB

[ S1223 series ]



KPINB0143EB


[ S12271 ]



KPINB0386EB


### Terminal capacitance vs. reverse voltage

[ S5821 series, S3071, S3072 ]




KPINB0344EA

[ S1223 series ]



KPINB0146EA

[ S12271 ]











KPINB0389EB

# Multi-element type Si photodiodes

## Segmented type Si PIN photodiodes

These Si PIN photodiode arrays consist of 2 or 4 elements having sensitivity in the UV to near IR range.

(Typ. Ta=25 °C)


Type no.	Number of elements	Photosensitive area size (mm)	Photosensitivity (A/W)	Cutoff frequency VR=10 V RL=50 Ω (MHz)	Dark current VR=10 V max. (nA)	Terminal capacitance VR=10 V f=1 MHz (pF)	Package	Photo
S3096-02	2	1.2 × 3 /2-seg- ment 	0.39 (λ=650 nm)	25	0.5*1	5	Plastic	
S4204		1 × 2 /2-seg- ment 	0.45 (λ=650 nm)	30	1*1	3		
S9345		1.5 × 1.5 + 1.5 × 4.1 	0.45 (λ=650 nm)	15	5*1	4 (Photo- diode A)   10 (Photo- diode B)		
S4349*2	4	3 × 3 /4-seg- ment 	0.45 (λ=720 nm)	20 (VR=5 V)	0.2 (VR=5 V)	25 (VR=5 V)	TO-5	

\*1: Total number of elements

\*2: Refer to "Precautions against UV light exposure" (P.45).


## Spectral response

[ S3096-02, S4204 ]




KMPDB0134EE

[ S9345 ]



KPINB0336ED


[ S4349 ]



KMPDB0126EB


## Dark current vs. reverse voltage

[ S3096-02, S4204 ]




KMPDB0136ED

[ S9345 ]



KPINB0295EA









[ S4349 ]



KMPDB0128EA

One-dimensional photodiode arrays (UV to near IR: UV sensitivity enhanced type)


These are Si photodiode linear arrays having rectangular elements equally spaced at a pitch of about 1 mm. (Typ. Ta=25 °C)

Type no.	Number of elements	Element pitch (mm)	Element size W × H (mm)	Spectral response range (nm)	Photosensitivity $\lambda=960$ nm (A/W)	Dark current $V_R=10$ mV max. (pA)	Terminal capacitance $V_R=0$ V $f=10$ kHz (pF)	Package	Photo		
S4111-16Q*2 S4111-16R	16	1.0	0.9 × 1.45	190 to 1100	0.58	5	200	Ceramic			
S4111-35Q*2	35			340 to 1100							
S4111-46Q*2	46		0.9 × 4.4	190 to 1100		10	550				
S4114-35Q*2	35			190 to 1000		0.50 ( $\lambda=800$ nm)	60		35		
S4114-46Q*2	46										
S12858-021 S12859-021	16	1.17	0.77 × 2.5	340 to 1100	0.61 ( $\lambda=920$ nm)	30	30	Glass epoxy (unsealed)			
S11299-021 S11212-021		1.575	1.175 × 2.0						30	40	
S12362-021 S12363-021		2.5	2.2 × 2.7						50	75	

\*2: Refer to "Precautions against UV light exposure" (P.45).


Spectral response

[ S4111/S4114 series ]



KMPD80112EC


[ S12858/S12859/S12362/S12363/S11212/S11299-021 ]



KMPD80357EB


Structure of photosensitive area (unit: mm)

[ S4111/S4114 series ]



KMPDA0227EC

[ S11212/S11299-021 ]







KMPDA0228EC

# Surface mount type Si photodiodes










## High-speed response Si PIN photodiodes

These are photodiodes sealed in a chip carrier package suitable for surface mounting and allowed solder reflow mounting on PC boards for automated processes. (Typ. Ta=25 °C)

Type no.	Cutoff frequency VR=10 V (MHz)	Photosensitive area size (mm)	Spectral response range (nm)	Photosensitivity λ=960 nm (A/W)	Terminal capacitance VR=10 V f=1 MHz (pF)	Package	Photo
S5106	20	5 × 5	320 to 1100	0.72	40	Ceramic	
S5107	10	10 × 10			150		
S7509	20	2 × 10			40		
S7510	15	6 × 11			80		

## Segmented type Si photodiodes


These Si photodiodes consist of 2, 4 or 16 elements and are integrated into a chip carrier package. (Typ. Ta=25 °C)

Type no.	Number of elements	Photosensitive area size (mm)	Spectral response range (nm)	Photosensitivity λ=960 nm (A/W)	Cutoff frequency VR=10 V (MHz)	Terminal capacitance VR=10 V f=1 MHz (pF)	Package	Photo
S5980	4	5 × 5 /4-seg- ment 	320 to 1100	0.72	25	10	Ceramic	
S5981		10 × 10 /4-seg- ment 			20	35		
S5870	2	10 × 10 /2-seg- ment 			10	50		
S8558	16	2 × 12.7 /16-seg- ment 			380 to 1100	0.63		25
 S15158			60 (Total of all elements)					




## Spectral response

[ S5106, S5107, S7509, S7510, S5980, S5981, S5870 ]



KPINB0165EB


[ S8558, S15158 ]



KMPDB0193EC

## Terminal capacitance vs. reverse voltage

[ S5106, S5107, S7509, S7510 ]



KPINB0128EA

## Small package type Si photodiodes






These surface mount type Si photodiodes are mounted on small packages. They are tape packaged and allows solder reflow mounting.

(Typ. Ta=25 °C)

Type no.	Photosensitive area size (nm)	Spectral response range (nm)	Photosensitivity $\lambda=960$ nm (nm)	Terminal capacitance $V_R=0$ V $f=10$ kHz (pF)	Package	Photo
S9674	2 × 2	320 to 1100	0.7	500	Glass epoxy	
<b>NEW</b> S9981-01CT	1.3 × 1.3		0.65	200		
S10625-01CT			0.54 ( $\lambda=940$ nm)			


## Small package type Si PIN photodiodes

These surface mount type Si PIN photodiodes are mounted on small packages. They are tape packaged and allows solder reflow mounting. (Typ. Ta=25 °C)


Type no.	Photosensitive area size (mm)	Spectral response range (nm)	Photosensitivity $\lambda=960$ nm (A/W)	Terminal capacitance f=1 MHz (pF)	Package	Photo
S13773	$\phi 0.8$	380 to 1000	0.54 ( $\lambda=800$ nm)	3 ( $V_R=10$ V)	Glass epoxy	
<b>NEW</b> S15193			0.64 ( $\lambda=920$ nm)	2 ( $V_R=10$ V)		
S10993-02CT	1.06 × 1.06	380 to 1100	0.6	6 ( $V_R=2.5$ V)		
S12158-01CT	2.77 × 2.77	320 to 1100	0.7	15 ( $V_R=12$ V)		
<b>NEW</b> S13954-01CT	$\phi 1.5$	320 to 1000	0.5 ( $\lambda=780$ nm)	13 ( $V_R=3$ V)		
<b>NEW</b> S14016-01DT	2.1 × 1.8	320 to 1100	0.7	12 ( $V_R=5$ V)	Plastic	

### Spectral response

[ S9674, S9981-01CT, S10625-01CT ]




[ S13773, S15193, S10993-02CT, S12158-01CT, S13954-01CT, S14016-01DT ]




### Dark current vs. reverse voltage

[ S9674, S9981-01CT, S10625-01CT ]



[ S13773, S15193, S10993-02CT, S12158-01CT, S13954-01CT, S14016-01DT ]







# Si photodiodes with preamp, TE-cooled type Si photodiodes

## Si photodiodes with preamp for measurement

These are low noise photosensors incorporating a large area Si photodiode, op amp and feedback capacitance.


(Typ.  $T_a=25\text{ }^\circ\text{C}$ )

Type no.	Cooling temperature $\Delta T$ ( $^\circ\text{C}$ )	Photosensitive area size (mm)	Spectral response range (nm)	Photosensitivity (V/nW)		NEP $\lambda=\lambda_p, f=10\text{ Hz}$ ( $\text{fW}/\text{Hz}^{1/2}$ )	Built-in feedback resistance ( $\text{G}\Omega$ )	Package	Photo
				$\lambda=200\text{ nm}$	$\lambda=960\text{ nm}$				
S8745-01*	Non-cooled	$2.4 \times 2.4$	190 to 1100	0.12	0.52	11	1	Metal	
S8746-01*		$5.8 \times 5.8$				15			
S9295*	50	$10 \times 10$		0.9	5.1	4	10		
S9295-01*	30			5					

\* Refer to "Precautions against UV light exposure" (P.45).


## NEP (noise equivalent power) vs. frequency

[ S8745-01 ]




KSPDB0237EA

[ S8746-01 ]



KSPDB0238EA

[ S9295 series ]





KSPDB0230EC

## TE-cooled type Si photodiodes


These photosensors combine a UV to near infrared Si photodiode with a TE-cooler and deliver low dark current.

(Typ.  $T_a=25\text{ }^\circ\text{C}$ )


Type no.	Cooling temperature $\Delta T$ ( $^\circ\text{C}$ )	Photosensitive area size (mm)	Spectral response range (nm)	Peak sensitivity wavelength (nm)	Dark current $V_R=10\text{ mV}$ ( $\mu\text{A}$ )	NEP ( $\text{W}/\text{Hz}^{1/2}$ )	Package	Photo
S2592-03*	35	$2.4 \times 2.4$	190 to 1100	960	10	$8.1 \times 10^{-15}$	TO-8	
S2592-04*		$5.8 \times 5.8$			25	$1.3 \times 10^{-14}$		
S3477-03*		$2.4 \times 2.4$			10	$8.1 \times 10^{-15}$	TO-66	
S3477-04*		$5.8 \times 5.8$			25	$1.3 \times 10^{-14}$		

\* Refer to "Precautions against UV light exposure" (P.45).

### Spectral response



### Thermistor temperature characteristics























# Si photodiodes for X-ray detection

## Si photodiodes with scintillator

These detectors are comprised of a Si photodiode coupled to a scintillator. Ceramic scintillators have sensitivity to X-rays about 1.2 times higher than CWO and offer high reliability. CsI scintillators also have high sensitivity and are low-cost.


The S11212 and S11299 series photodiode arrays have a back-illuminated structure. They realize superb spectral response and sensitivity uniformity compared to our previous products.

(Typ. Ta=25 °C)


Type no.	Scintillator	Number of elements	Element pitch (mm)	Element size W × H (mm)	Dark current max. VR=10 mV (pA)	X-ray sensitivity* (nA)	Package	Photo
S8559	CsI(Tl)	1	-	5.8 × 5.8	50	52	Ceramic	
S8193	GOS ceramic					30		
S12858-122	CsI(Tl)	16	1.17	0.77 × 2.5	30	5.0	Glass epoxy	
S12859-122								
S12858-324	GOS ceramic					2.5		
S12859-324								
S12858-422	Phosphor sheet					2.2		
S12859-422								
S11299-121	CsI(Tl)	16	1.575	1.175 × 2.0	30	6.0	Glass epoxy	
S11212-121								
S11299-321	GOS ceramic					3.5		
S11212-321								
S11299-422	Phosphor sheet					3.0		
S11212-422								
S12362-121	CsI(Tl)	16	2.5	2.2 × 2.7	50	12.5	Glass epoxy	
S12363-121								
S12362-321	GOS ceramic					7.2		
S12363-321								
S12362-421	Phosphor sheet					6.0		
S12363-421								

\* These are for reference (X-ray tube voltage: 120 kV, tube current: 1.0 mA, aluminum filter t=6 mm, distance: 830 mm), X-ray sensitivity depends on the X-ray equipment operating and setup conditions.

**Spectral response (S12858/S12859/S11212/S11299/S12362/S12363 series)**



**Uniformity (S11212/S11299 series)**




KMPD80361EC

\* The characteristics exclude the scintillator but include the transmittance and reflectance of the adhesive resin used to bond a scintillator.

KMPD80360ED


**Emission spectrum of scintillator and spectral response**

[ S11212/S11299-121 [CsI(Tl)] ]



KSPD80282EE

[ S11212/S11299-321 (GOS ceramic) ]



KSPD80281EE

**▲ Typical scintillator characteristics**

Parameter	Condition	CsI(Tl)	GOS ceramic	Unit
Peak emission wavelength		560	512	nm
X-ray absorption coefficient	100 keV	10	7	cm <sup>-1</sup>
Refractive index	$\lambda = \lambda_0 n$	1.7	2.2	-
Decay constant		1	3	$\mu$ s
Afterglow	100 ms after X-ray turn off	0.3	0.01	%
Density		4.51	7.34	g/cm <sup>3</sup>
Color		Transparent	Light yellow-green	-
Sensitivity nonuniformity		$\pm 10$	$\pm 5$	%



## Large area Si PIN photodiodes


These Si PIN photodiodes, mounted on a white ceramic base, are specifically developed for applications in high energy physics and are mainly used being coupled to a scintillator. Because of high resistance to high voltages, these Si PIN photodiodes operate at high reverse voltages allowing a high-speed response despite the large photosensitive areas.

The S3590-18/-19 are violet sensitivity enhanced type and the S3590-19 is an unsealed type. To improve photodiode-to-scintillator coupling efficiency, we also offer the S8650 with epoxy resin coating window processed to have a flat surface. (Typ.  $T_a=25\text{ }^\circ\text{C}$ )


Type no.	Window	Photosensitive area size (mm)	Depletion layer thickness $V_R=70\text{ V}$ (mm)	Spectral response range (nm)	Photosensitivity $\lambda=960\text{ nm}$ (A/W)	Dark current max. $V_R=70\text{ V}$ (nA)	Terminal capacitance $V_R=70\text{ V}$ $f=1\text{ MHz}$ (pF)	Package	Photo
S3590-08	Epoxy resin	10 × 10	0.3	340 to 1100	0.66	6	40	Ceramic	
S3590-09	Unsealed								
S3590-18	Epoxy resin				0.65	10			
S3590-19	Unsealed								
S8650	Epoxy resin				0.66	6			

## Spectral response


[ S3590-08, S8650 ]



[ S3590-09 ]




[ S3590-18/-19 ]




## Terminal capacitance vs. reverse voltage





[ S3590 series, S8650 ]



## Emission spectrum of scintillators and spectral response (S3590-08)




(Typ. Ta=25 °C)

Type no.	Window	Photosensitive area size (mm)	Depletion layer thickness VR=70 V (mm)	Spectral response range (nm)	Photosensitivity λ=960 nm (A/W)	Dark current max. VR=70 V (nA)	Terminal capacitance VR=70 V f=1 MHz (pF)	Package	Photo				
S2744-08	Epoxy resin	10 × 20	0.3	340 to 1100	0.66	10	85	Ceramic					
S2744-09	Unsealed												
S3204-08	Epoxy resin	18 × 18							20	130	30	300	
S3204-09	Unsealed												
S3584-08	Epoxy resin	28 × 28							30	300	10	40	
S3584-09	Unsealed												
S3588-08	Epoxy resin	3 × 30							10	40	10	40	
S3588-09	Unsealed												


### Spectral response

[ S2744/S3588 series ]



KPINB0265EE


[ S3204/S3584 series ]



KPINB0277EC


### Terminal capacitance vs. reverse voltage

[ S2744/S3588 series ]



KPINB0222EA

[ S3204/S3584 series ]



KPINB0230EC




## Large area type Si PIN photodiodes for direct radiation detection


These are unsealed type large area Si PIN photodiodes for direct radiation detection. High energy radiation can be detected with high efficiency. (Typ. Ta=25 °C)

Type no.	Window	Photosensitive area size (mm)	Depletion layer thickness (mm)	X-ray energy max. (keV)	Dark current max. (nA)	Package	Photo
S13993	None	10 × 10	0.3	50	6	Ceramic	
S14605		9 × 9	0.5		30		

### Photosensitivity vs. X-ray energy (theoretical value)



### Terminal capacitance vs. reverse voltage








# Special application Si photodiodes

## RGB color sensors

These photosensors are color sensors using a 3-element photodiode with color sensitivity, assembled in one package.

(Typ. Ta=25 °C)


Type no.	Spectral response range		Peak sensitivity wavelength (nm)	Photosensitivity $\lambda=\lambda_p$ (A/W)		Dark current $V_R=1\text{ V}$ Total number of elements max. (pA)	Photosensitive area size (mm)		Package	Photo
	Blue	Green		Blue	Green		Blue	Green		
S7505-01	Blue	400 to 540	460	Blue	0.18	200	Blue	$1.5 \times 1.5 (\times 2)$	Surface mount type plastic	
	Green	480 to 600	540	Green	0.23		Green	$1.5 \times 1.5$		
	Red	590 to 720	620	Red	0.16		Red	$1.5 \times 1.5$		
S9032-02*1	Blue	400 to 540	460	Blue	0.18	100	$\phi 2 / 3\text{-segment}$		Surface mount type plastic	
	Green	480 to 600	540	Green	0.23					
	Red	590 to 720	620	Red	0.16					
S9702*1	Blue	400 to 540	460	Blue	0.18	50	$1 \times 1 / 3\text{-segment}$		Surface mount type, small plastic	
	Green	480 to 600	540	Green	0.23					
	Red	590 to 720	620	Red	0.16					
S10917-35GT	Blue	390 to 530	460	Blue	0.2	50	$1 \times 1 / 3\text{-segment}$		Surface mount type, small, glass epoxy	
	Green	470 to 600	540	Green	0.23					
	Red	590 to 680	620	Red	0.17					
S10942-01CT	See the spectral response.			Blue	$0.21^{*2}$	50	$1 \times 1 / 3\text{-segment}$		Surface mount type, small glass epoxy	
				Green	$0.25^{*2}$					
				Red	$0.45^{*2}$					

\*1: If excessive vibration is continuously applied to the glass filter, there is a risk that the filter may come off, so secure the glass filter with a holder.


\*2: Blue:  $\lambda=460\text{ nm}$ , Green:  $\lambda=540\text{ nm}$ , Red:  $\lambda=640\text{ nm}$

## Spectral response


[ S7505-01, S9032-02, S9702 ]



[ S10917-35GT ]






[ S10942-01CT ]




This sensor also has sensitivity in the infrared region, so cut off infrared light as needed.

The S6428-01, S6429-01 and S6430-01 are monochromatic color sensors sensitive to blue, green and red light, respectively.

(Typ. Ta=25 °C)

Type no.	Spectral response range (nm)	Peak sensitivity wavelength (nm)	Photosensitivity $\lambda=\lambda_p$ (A/W)	Dark current $V_R=1\text{ V}$ max. (pA)	Photosensitive area size (mm)	Package	Photo
S6428-01	400 to 540	460	0.22	20	2.4 × 2.8	Plastic	
S6429-01	480 to 600	540	0.27				
S6430-01	590 to 720	660	0.45				

### Spectral response






KSPDB0280EC

## Violet/blue sensitivity enhanced type


These are photodiodes for violet/blue laser diode detection.

(Typ.  $T_a=25\text{ }^\circ\text{C}$ )


Type no.	Cutoff frequency (MHz)	Photosensitive area size (mm)	Peak sensitivity wavelength (nm)	Photo-sensitivity (A/W)	Dark current max. (nA)	Terminal capacitance $f=1\text{ MHz}$ (pF)	Package	Photo
S5973-02	1 GHz ( $V_R=3.3\text{ V}$ )	$\phi 0.4$	760	0.3 ( $\lambda=410\text{ nm}$ )	0.1 ( $V_R=3.3\text{ V}$ )	1.6 ( $V_R=3.3\text{ V}$ )	TO-18	
S9195	50 ( $V_R=10\text{ V}$ )	$5 \times 5$	840	0.28 ( $\lambda=405\text{ nm}$ )	5 ( $V_R=10\text{ V}$ )	60 ( $V_R=10\text{ V}$ )	TO-8	
S3994-01	20 ( $V_R=30\text{ V}$ )	$10 \times 10$	960	0.25 ( $\lambda=400\text{ nm}$ )	10 ( $V_R=30\text{ V}$ )	40 ( $V_R=30\text{ V}$ )	Ceramic	

## Spectral response


[ S5973-02 ]



[ S9195 ]




[ S3994-01 ]




## Dark current vs. reverse voltage


[ S5973-02 ]



[ S9195 ]





[ S3994-01 ]



For VUV (vacuum ultraviolet) monitor

These Si photodiodes are specially optimized for excimer laser monitor (ArF: 193 nm, KrF: 248 nm): sensitive in the vacuum UV (VUV) range. (Typ. Ta=25 °C)


Type no.	Photosensitivity $\lambda=193$ nm (A/W)	Dark current VR=10 mV max. (nA)	Photosensitive area size (mm)	Package	Photo
S8552*	0.06	1.0	10 × 10	Ceramic (unsealed)	
S8553*		5.0	18 × 18		

\* Refer to "Precautions against UV light exposure ㉔" (P.45).

For VUV detection (high reliability type)


The S10043 is greatly improved in sensitivity stability even after exposure to ArF ( $\lambda=193$  nm) excimer laser.

(Typ. Ta=25 °C)


Type no.	Photosensitivity $\lambda=193$ nm (A/W)	Dark current VR=10 mV max. (nA)	Photosensitive area size (mm)	Package	Photo
S10043*	0.015	1.0	10 × 10	Ceramic (unsealed)	

\* Refer to "Precautions against UV light exposure ㉔" (P.45).

Variation in sensitivity due to UV exposure






Spectral response



## For monochromatic light detection


This photosensor uses an interference filter and has high sensitivity only to monochromatic light.

(Typ. Ta=25 °C)

Type no.	Peak sensitivity wavelength (nm)	Spectral response half-width (nm)	Photosensitivity $\lambda$ =Center wavelength (mA/W)	Dark current $V_R=10$ mV max. (pA)	Photosensitive area size (mm)	Package	Photo
S12742-220*1	220	10	6	25	3.61 × 3.61	TO-5	
S12742-254*1	254		18				
S12742-275*1	275		10				

\*1: Refer to "Precautions against UV light exposure" (P.45).

## Spectral response




KSPDB0390EA

Note: The photosensor can be customized to support other wavelength types, including center wavelengths of 340 nm and 560 nm. (made-to-order product).


## For YAG laser detection

This is a Si PIN photodiode developed to measure infrared energy emitted from YAG lasers (1.06  $\mu$ m).

(Typ. Ta=25 °C)


Type no.	Photosensitive area size (mm)	Spectral response range (nm)	Peak sensitivity wavelength (nm)	Photosensitivity $\lambda=1060$ nm (A/W)	Dark current $V_R=100$ V max. (nA)	Rise time $\lambda=1060$ nm $V_R=100$ V, $R_L=50$ $\Omega$ (ns)	Package	Photo
S3759	$\phi 5$	360 to 1120	980	0.38	10	12.5	TO-8	

## Spectral response



KPINB0279EB

## Response waveform





KPINB0280EC

### For electron beam detector


These photodiodes directly detect low energy (1 keV or more) electron beams with high sensitivity. The structure with an extremely thin dead layer (insensitive layer) makes these photodiodes ideal for backscattered electron detector for Scanning Electron Microscope (SEM).

(Typ. Ta=25°C)

Type no.	Incident electron energy range (keV)	Output current (nA)	Dark current VR=5 V max. (nA)	Terminal capacitance VR=5 V (pF)	Cutoff frequency VR=5 V (MHz)	Electron multiplying gain	Package	Photo
S11141-10	1 to 30	30 (Electron energy: 1.5 keV Ip*2=100 pA)	60	450	2.5	300 (Electron energy: 1.5 keV)	Thin ceramic (unsealed)	
S11142-10				200	5			


\*2: Probe current

### Gain vs. electron energy



KSPDB0344EA

### Electron multiplication principle





Electrons generate ions as they pass through silicon. This ionization process generates a large number of electron-hole pairs that then multiply the number of electrons. The electron multiplication can boost the output current by approximately 300 times at an input electron energy of 1.5 keV (refer to "Gain vs. electron energy").

KSPDC0089EA

### PWB package with leads type


The S12497 and S12498 are Si photodiodes suitable for non-destructive inspection of baggage and the like and general industrial measurement. As they are back-illuminated photodiodes, photosensitive area does not have wires, and therefore a scintillator can be mounted directly on the photodiode.

(Typ. Ta=25 °C)

Type no.	Photosensitive area (mm)	Spectral response range (nm)	Peak sensitivity wavelength (nm)	Photo-sensitivity λ=920 nm (A/W)	Short circuit current 100 lx, 2856 K (μA)	Terminal capacitance VR=0 V, f=10 kHz (pF)	Photo
S12497	9.5 × 9.5	400 to 1100	920	0.57	75	950	
S12498	6 × 6				30	380	

### Spectral response




[ S12497, S12498 ]



KSPDB0360EC


## CSP type

These are back-illuminated photodiodes employing a CSP (chip size package) that allows direct coupling of a scintillator on the chip. It is designed with minimal dead space around the product. This makes it possible to arrange multiple products side by side. (Typ. Ta=25 °C)

Type no.	Photosensitive area size (mm)	Spectral response range (nm)	Peak sensitivity wavelength (nm)	Photo-sensitivity $\lambda=920$ nm (A/W)	Short circuit current 100 lx, 2856 K ( $\mu$ A)	Terminal capacitance $V_R=0$ V, $f=10$ kHz (pF)	Package	Photo
S13955-01	7.37 × 7.37	400 to 1100	960	0.61	46	500	PWB (unsealed)	
S13956-01	2.5 × 2.5				5.5	60		
S13957-01	4.5 × 4.5				22	230		



## CSP type 64-element Si photodiode array

This is an 8 × 8 element Si photodiode array with a back-illuminated type structure for X-ray non-destructive inspection. A scintillator can be directly coupled on the chip. It is designed with minimal dead space around the product. This makes it possible to arrange multiple products side by side. Moreover, there is no crosstalk between channels. (Typ. Ta=25 °C)

Type no.	Number of elements	Element pitch (mm)	Element size W × H (mm)	Spectral response range (nm)	Peak sensitivity wavelength (nm)	Photo-sensitivity $\lambda=920$ nm (A/W)	Short circuit current 100 lx, 2856 K ( $\mu$ A)	Terminal capacitance $V_R=0$ V, $f=10$ kHz (pF)	Package	Photo
S13620-02	64 (8 × 8)	3.0	2.5 × 2.5	400 to 1100	960	0.61	5.5	60	PWB (unsealed)	

## 6-element array for encoder


This is a surface mount type 6-element Si PIN photodiode. The six elements are separated individually and arranged so that they are suitable for the incremental encoder. (Typ. Ta=25 °C)

Type no.	Number of elements	Element size W × H (mm)	Spectral response range (nm)	Peak sensitivity wavelength (nm)	Photo-sensitivity $\lambda=960$ nm (A/W)	Terminal capacitance $V_R=10$ V, $f=10$ kHz (pF)	Package	Photo
 S14833	6	2.76 × 1.37	340 to 1100	960	0.68	9	Glass epoxy	


## Spectral response

[ S13955-01, S13956-01, S13957-01, S13620-02 ]

[ S14833 ]



KSPDB0367EB



KSPDB0570EA



# Related products of Si photodiode

## RGB color sensor modules

### For TFT-LCD monitor


#### ● RGB-LED backlight monitor for TFT-LCD (liquid crystal display)

##### Features

- Built-in RGB color sensor (S9032-02)  
Sensitivity matches wavelengths of RGB-LED backlight for TFT-LCD.
- 3 ch current-to-voltage amplifiers  
Simultaneous output of 3 ch RGB photocurrent
- Configuration and size suitable for side mounting to TFT-LCD
- Low current consumption: 0.4 mA typ.  
(1/3 than the conventional type)
- High gain type (C9303-04)

##### Applications

- RGB-LED backlight monitor for TFT-LCD



(Typ. Ta=25 °C)

Type no.	Photosensitivity (V/mW)			Cutoff frequency -3 dB (kHz)	Supply voltage (V)
	$\lambda_p=620$ nm	$\lambda_p=540$ nm	$\lambda_p=460$ nm		
C9303-03	-14	-20	-18	16	+2.7 to +5.5
C9303-04	-108	-156	-122	2.4	

### Simple color measurement

#### ● Numerically converts RGB color information and outputs data for PCs

##### Features

- Measures object color information as a reflective type\*
- Measures small areas using an objective optical fiber
- 12-bit digital output
- Serial connection (RS-232C) with PC
- Teaching function
- Sample software included

##### Applications

- Color monitoring and simple detection of color difference of opaque body (painting, printing, cosmetics, etc.)
- Teaching material for simple color measurements



(Typ. Ta=25 °C)

Type no.	Light source	Photosensor	Measurement and output cycle (ms)	Supply voltage (V)
C9315	White LED	Si photodiode	200	AC adapter (+12)

\* Does not conform to CIE (International Commission on Illumination) standards

## Color sensor evaluation circuit

#### ● Color sensor evaluation circuit board

##### Features

- 3 ch current-to-voltage conversion amplifier for color sensor evaluation
- Color sensors that mount on C9331:  
S7505-01, S9032-02 (sold separately)

##### Applications

- Evaluation of Hamamatsu color sensor



(Ta=25 °C, Vcc=9.0 V, common to each RGB channel)

Type no.	Output offset voltage $Z_t=5.1 \times 10^5$ V/A [without photodiode] (mV)		Conversion impedance (V/A)	Cutoff frequency [without photodiode] -3 dB (kHz)	Supply voltage (V)
	Typ.	Max.			
C9331	±40	±50	$1 \times 10^5$ to $5.1 \times 10^5$	14	+7 to +15

## Driver circuit for Si photodiode array

### ● Driver circuit for 16-element photodiode array

#### Features

- High precision and high-speed measurement by simultaneous 16-channel readout
- Assembled with pulse generator (8-step adjustable oscillatory frequency)  
CLK, START, A/D conversion Trig and EOS pulse output
- Choice of gain (conversion impedance):  $1 \times 10^6$  V/A or  $1 \times 10^7$  V/A
- Accessory AC adapter (+12 V) operation



Type no.	Applicable sensor
C9004	Hamamatsu S4111-16 series, S11212 series photodiode arrays are directly mountable on board.

## Photodiode modules

### ● Integrates a Si photodiode for precision photometry with low-noise amplifier.

The C10439 series is a high-precision photodetector that combines a photodiode and current-to-voltage conversion amplifier.

#### Features

- Easy handling  
The output from these photodiode modules is an analog voltage and can be checked with a voltmeter, etc.
- Two switchable photosensitivity ranges  
High accuracy output can be obtained by selecting a range suitable for the light level to be detected.
- Compact size  
Half the size of a business card (C10439-15: business card size) Can be mounted directly on optical bench rod (M4).



Type no.	Photosensitive area size (mm)	Peak sensitivity wavelength (nm)	Photosensitivity $\lambda=\lambda_p$ (mV/nW)	Conversion impedance (V/A)	Cutoff frequency -3 dB (Hz)	Supply voltage (V)	Dimensions W x D x H (mm)
C10439-01	2.4 x 2.4	960	H: 500 L: 5	H: $10^9$ L: $10^7$	H: 10 L: 1k	External power supply $\pm 5$ to $\pm 12$	19 x 46 x 52
C10439-02	5.8 x 5.8						
C10439-03	10 x 10						
C10439-07	2.4 x 2.4						
C10439-08	5.8 x 5.8						
C10439-09	10 x 10						
C10439-10	$\phi 1$	1550	H: 0.5 L: 0.005	H: $10^6$ L: $10^4$	H: 1k L: 100k*1		19 x 50 x 52
C10439-11	$\phi 3$						
C10439-14	0.7 x 0.7	4100	H: 0.045*2 L: 0.0045*2	H: $10^7$ L: $10^6$	H: 100 L: 1k		19 x 50 x 75
C10439-15	Si	2.4 x 2.4	H: 0.45 L: 0.045	H: $10^6$ L: $10^5$	H: 10k L: 100k*1		
	InGaAs	$\phi 1$	2300				

(Typ.  $T_a=25$  °C)

\* 1: Output amplitude: 2 Vp-p \* 2: Uniform irradiation on the entire photosensitive area

## Signal processing unit for photodiode module

### ● Unit dedicated for photodiode module (C10439 series)

The C10475 converts the output from a photodiode module (C10439 series) into digital signals. Also supplies power to the photodiode module.

#### Features

- High-resolution digital output (16-bit)
- Data logger function



Type no.	Digital output	Minimum measurement time interval (ms)	Supply voltage (V)	Dimensions W x D x H (mm)
C10475	Conforms to RS-232C (16-bit)	50	AC adapter (+12) or battery (+9)	110 x 100 x 30

(Typ.  $T_a=25$  °C)

Note: RS-232C cable is optional.

## Photosensor amplifier

### For low-light-level detection

- Digital output function, current-to-voltage conversion amplifier for amplifying very slight photocurrent with low noise

#### Features

- Three sensitivity ranges
- Selectable operation modes (analog output / digital output)
- Serial connection (RS-232C) with PC
- Data logger function, low battery function



Photodiode, coaxial cable with BNC-BNC plug and RS-232C cable are optional.

(Typ. Ta=25 °C)

Type no.	Range	Conversion impedance (V/A)	Cutoff frequency -3 dB (Hz)	Power supply (V)	Dimensions W × D × H (mm)
C9329	H	10 <sup>9</sup>	16	AC adapter (+12) or battery (+9)	115 × 90 × 40
	M	10 <sup>7</sup>	1600		
	L	10 <sup>5</sup>	1600		

### With optical fiber

- Light-to-voltage conversion amplifier with optical fiber

#### Features

- Easy handling  
Built-in photodiode allows easy detection of light just by connecting to a voltmeter, etc.
- Optical fiber light input  
Measures light at a narrow detection point. Separating the amplifier from the detection point allows measurement in unusual environments and achieves low noise.
- Three sensitivity ranges



(Typ. Ta=25 °C)

Type no.	Range	Photosensitivity λ=830 nm (mV/μW)	Conversion impedance (V/A)	Cutoff frequency -3 dB (MHz)	Power supply (V)	Dimensions W × D × H (mm)
C6386-01	H	30	10 <sup>5</sup>	1	External power supply (±15) or batteries (+9) × 2	115 × 90 × 40
	M	3	10 <sup>4</sup>	3		
	L	0.3	10 <sup>3</sup>	10		

### High-speed type

- Current-to-voltage conversion amplifier

#### Features

- C8366: for high speed Si PIN photodiode  
C8366-01: for high speed InGaAs photodiode
- Wide bandwidth: DC to 100 MHz typ. (-3 dB; varied by the photodiode used)
- Just inserting the photodiode leads makes the connection.  
(Compatible with TO-8, TO-5 and TO-18 packages)
- Adjustable response speed  
Response speed can be adjusted by a trimmer potentiometer easily.
- Compact size



(Typ. Ta=25 °C)

Type no.	Conversion impedance (V/A)	Cutoff frequency -3 dB (MHz)	Power supply (V)	Dimensions W × D × H (mm)
C8366	10 <sup>3</sup>	100	External power supply (±15)	19 × 52 × 46
C8366-01				

## Compact board type

- Current-to-voltage conversion amplifier for low-level-light




(Typ. Ta=25 °C)

Type no.	Conversion impedance (V/A)	Cutoff frequency -3 dB (Hz)	Power supply (V)	Dimensions W × D × H (mm)
C9051	$10^8$	16	AC adapter (+12)	50 × 50 × 19

## Charge amplifier

- For radiation and high energy particle detection

The H4083 is a low-noise hybrid charge amplifier designed for a wide range of spectrometric applications including soft X-ray and low to high energy gamma-ray spectrometry. The first stage of this amplifier uses a low-noise junction type FET, which exhibits excellent performance when used with a photodiode having a large junction capacitance. The H4083 is especially suited for use with Hamamatsu S3590/S3204 series, etc. Si PIN photodiodes. S3590 series photodiodes can be directly mounted on the backside of the H4083, so there will be no increase in stray capacitance.



### Features

- Low noise
- Compact and lightweight
- Easy handling

### Applications

- Detection of X-rays, radiation, high energy particles

(Typ. Ta=25 °C)

Type no.	Amplification method	Input/output polarity	Charge gain	Noise characteristic (e-/FWHM)	Negative feedback constant	Power supply (V)	Current consumption (mW)	Dimensions W × D × H (mm)
H4083	Charge-sensitive type	Inverted	0.5 V/pC 22 mV/MeV (Si)	550	50 MΩ//2 pF	±12	150	24 × 19 × 4

# Description of terms

## ▶ Spectral response

The photocurrent produced by a given level of incident light varies with the wavelength. This relation between the photoelectric sensitivity and wavelength is referred to as the spectral response characteristic and is expressed in terms of photosensitivity or quantum efficiency.

## ▶ Photosensitivity: S

This measure of sensitivity is the ratio of photocurrent expressed in amperes (A)—or output voltage expressed in volts (V)—to the incident light expressed in watts (W). It may be represented as either an absolute sensitivity (A/W or VW unit) or as a relative sensitivity normalized for the sensitivity at the peak wavelength, usually expressed in percent (%) with respect to the peak value. At Hamamatsu, we usually use absolute sensitivity to express photosensitivity, and the spectral response range is defined as the region in which the relative sensitivity is higher than 5% or 10% of the peak value.

## ▶ Quantum efficiency: QE

The quantum efficiency is the number of electrons or holes that can be detected as a photocurrent, divided by the number of incident photons. This is commonly expressed in percent (%). The quantum efficiency and photo sensitivity S have the following relationship at a given wavelength (nm):

$$QE = \frac{S \times 1240}{\lambda} \times 100 [\%]$$

## ▶ Short circuit current: I<sub>sc</sub>

The output current that flows through the photodiode when the load resistance is 0. This is often called "white light sensitivity" with regards to the spectral response, and a tungsten lamp of 2856 K distribution temperature (color temperature) is used for the light source. At Hamamatsu, we indicate the short circuit current at 100 lx illuminance in the table of characteristics in our catalogues.

## ▶ Open circuit voltage: Voc

The open circuit voltage is a photovoltaic voltage generated when the load resistance is infinite. The open circuit voltage depends on the light level, but for light levels higher than extremely low levels, it is nearly constant.

## ▶ Dark current: I<sub>D</sub>

The dark current is a small current which flows when a reverse voltage is applied to a photodiode even in dark state. This is a major source of noise for cases in which a reverse voltage is applied to photodiodes (PIN photodiode, etc.).

## ▶ Shunt resistance: R<sub>sh</sub>

The voltage-to-current ratio in the vicinity of 0 V in photodiodes. The shunt resistance is defined as follows: Where I<sub>D</sub> is the dark current at V<sub>R</sub>=10 mV.

$$R_{sh} [\Omega] = \frac{0.01 [V]}{I_D [A]}$$

For applications where no reverse voltage is applied, noise resulting from the shunt resistance becomes predominant.

## ▶ Terminal capacitance: C<sub>t</sub>

An effective capacitor is formed at the PN junction of a photodiode. Its capacitance is termed the junction capacitance and is one of parameters that determine the response speed of the photodiode. And it probably causes a phenomenon of gain peaking in I/V converter using operational amplifier. In Hamamatsu, the terminal capacitance including this junction capacitance plus package stray capacitance is listed.

## ▶ Rise time: tr

This is the measure of the time response of a photodiode to a stepped light input, and is defined as the time required for the output to change from 10% to 90% of the maximum light level (steady output level).

## ▶ Cutoff frequency: fc

The frequency at which the photodiode output decreases by 3 dB from the output in the frequency region where the output is constant. The rise time (tr) has a relation with the cut-off frequency (fc) as follows:

$$tr [s] = \frac{0.35}{fc [Hz]}$$

## ▶ NEP (noise equivalent power)

The NEP is the amount of light equivalent to the noise level of a device. It is the light level required to obtain a signal-to-noise ratio of unity. Our data sheets show the NEP values measured at the peak wavelength λ<sub>p</sub>. Since the noise level is proportional to the square root of the frequency bandwidth, the NEP is measured at a bandwidth of 1 Hz.

$$NEP [W/Hz^{1/2}] = \frac{\text{Noise current [A/Hz}^{1/2}]}{\text{Photosensitivity [A/W] at } \lambda_p}$$

## ▶ Maximum reverse voltage: V<sub>R max</sub>

Applying a reverse voltage to a photodiode triggers a breakdown at a certain voltage and causes severe deterioration of the device performance. Therefore the absolute maximum rating is specified for reverse voltage at the voltage somewhat lower than this breakdown voltage. The reverse voltage shall not exceed the maximum rating, even instantaneously.

## Reference (Physical constants related to light and opto-semiconductors)

Constant	Symbol	Value	Unit
Electron charge	q	1.602 × 10 <sup>-19</sup>	C
Speed of light in vacuum	c	2.998 × 10 <sup>8</sup>	m/s
Planck's constant	h	6.626 × 10 <sup>-34</sup>	J · s
Boltzmann's constant	k	1.381 × 10 <sup>-23</sup>	J/K
Thermal energy at room temperature	kT	0.0259 (300 K)	eV
Energy of 1 eV	eV	1.602 × 10 <sup>-19</sup>	J
Wavelength equivalent to 1 eV in vacuum	—	1240	nm
Permittivity of vacuum	ε <sub>0</sub>	8.854 × 10 <sup>-12</sup>	F/m
Relative permittivity of silicon	ε <sub>si</sub>	Approx. 12	—
Relative permittivity of silicon oxide film	ε <sub>ox</sub>	Approx. 4	—
Band gap energy of silicon	E <sub>g</sub>	Approx. 1.12 (25 °C)	eV

## Precautions against UV light exposure

- ① When UV light irradiation is applied, the product characteristics may degrade. Such examples include degradation of the product's UV sensitivity and increase in dark current. This phenomenon varies depending on the irradiation level, irradiation intensity, usage time, and ambient environment and also varies depending on the product model. Before employing the product, we recommend that you check the tolerance under the ultraviolet light environment that the product will be used in.
- ② Exposure to UV light may cause the characteristics to degrade due to gas released from the resin bonding the product's component materials. As such, we recommend that you avoid applying UV light directly on the resin and apply it on only the inside of the photosensitive area by using an aperture or the like.

## Related information

[www.hamamatsu.com/sp/ssd/doc\\_en.html](http://www.hamamatsu.com/sp/ssd/doc_en.html)

- Precautions
  - Disclaimer
  - Metal, ceramic, plastic package products
  - Unsealed products
  - Surface mount type products

## Disclaimer

- Products manufactured by Hamamatsu Photonics K.K. (hereafter “Hamamatsu”) are intended for use in general-use electronic devices (such as measurement equipment, office equipment, information communications equipment, household appliances, etc.). Unless an exception to the following is stated in the documentation of a specific product, Hamamatsu products are not to be used for special applications which demand extremely high reliability or safety (such as equipment for nuclear power control, aerospace equipment, medical equipment and transportation equipment that directly affect human life, or disaster prevention or safety equipment).
- Hamamatsu products should not be used in excess of their absolute maximum ratings. Attention must be paid to all documented precautions.
- Hamamatsu continually makes efforts to improve the quality and reliability of its products; however these efforts cannot ensure 100% compliance with the manufacturing specifications. Sufficient safety design (such as redundant safety, fire preventative, and malfunction preventative features) are to be implemented in the development of equipment manufactured with the Hamamatsu product so that personal injury, fire, or damage to public property or welfare does not occur in the unlikely event of a malfunction of the Hamamatsu product. A dangerous condition could be created if sufficient consideration is not given to safety design that addresses potential problems, especially in the design of equipment where the failure or malfunction of the Hamamatsu product within the equipment could result in bodily harm, life-threatening injury, or serious property damage during the use of the equipment. With such types of equipment, Hamamatsu shall not be responsible for the use of its products within the equipment in any way for not obtaining our written consent such as specification sheets beforehand.
- Appropriate descriptions of the functions, performance, and methods of operation of the Hamamatsu product and the equipment within which the Hamamatsu product is incorporated are to be provided to end-users of the equipment. All accompanying warnings and cautionary labeling are also to be provided to the end-user.
- Warranty of the Hamamatsu product is limited to the repair or replacement of a product in which a defect is discovered within 1 year of delivery of the product and notification is made to Hamamatsu within that period, otherwise certain warranty is specified. However, even within the warranty period Hamamatsu shall not be responsible for damages caused by either natural disaster or improper use of the product (such as modification of the product or any use that contravenes the operating conditions, intended applications, operating instructions, storage method, disposal method, or any other term or condition described in our products’ documents). For a complete description of the warranty associated with a particular product, please contact your regional Hamamatsu sales office.
- Exportation of some Hamamatsu products must comply with individual governmental regulations pertaining to export control. Export in contravention of governmental regulations is a crime and can result in severe monetary penalties or imprisonment. While we cannot give any legal advice as to how to comply with these regulations, we can help classify the goods in order to assist the buyer in determining what regulations apply. Please contact your regional Hamamatsu sales office for further assistance.
- In our products’ documents, applications are mentioned as notable examples of how the Hamamatsu product can be used. Such mentions guarantee neither the suitability of the product for specific purposes nor the success or failure of the commercial use of the product in specific applications. Some applications may be protected by patents or other proprietary rights. Hamamatsu assumes no liability for any infringing use of our products. All warranties express or implied, including any warranty of merchantability or fitness for any particular purpose are hereby excluded.
- Product specifications are subject to change without notification due to product improvements, etc. Our products’ documents have been carefully prepared to ensure the accuracy of the technical information contained herein, but in rare cases there may be errors. When using the Hamamatsu product, please be sure to request the delivery specification sheets, and confirm upon delivery that it is the most recent specifications. In addition to this document, please be sure to read any accompanying technical documentation and make note of any precautions listed in the delivery specification sheets.
- All Rights Reserved, transfer or duplication of the contents of our products’ documents without the permission of Hamamatsu is prohibited.

## Main Products

### Opto-semiconductors

Si photodiodes  
 APD  
 MPPC  
 Photo IC  
 Image sensors  
 PSD  
 Infrared detectors  
 LED  
 Optical communication devices  
 Automotive devices  
 X-ray flat panel sensors  
 Mini-spectrometers  
 Opto-semiconductor modules

### Electron tubes

Photomultiplier tubes  
 Photomultiplier tube modules  
 Microchannel plates  
 Image intensifiers  
 Xenon lamps / Mercury xenon lamps  
 Deuterium lamps  
 Light source applied products  
 Laser applied products  
 Microfocus X-ray sources  
 X-ray imaging devices

### Imaging and processing systems

Cameras / Image processing measuring systems  
 X-ray products  
 Life science systems  
 Medical systems  
 Semiconductor failure analysis systems  
 FPD / LED characteristic evaluation systems  
 Spectroscopic and optical measurement systems

### Laser products

Semiconductor lasers  
 Applied products of semiconductor lasers  
 Solid state lasers

## Sales Offices

#### ■ Japan:

**HAMAMATSU PHOTONICS K.K.**  
 325-6, Sunayama-cho, Naka-ku,  
 Hamamatsu City, Shizuoka Pref. 430-8587, Japan  
 Telephone: (81)53-452-2141, Fax: (81)53-456-7889  
 E-mail: intl-div@hq.hp.k.co.jp

#### ■ China:

**HAMAMATSU PHOTONICS (CHINA) Co., Ltd.**  
 Main Office  
 1201 Tower B, Jiaming Center, 27 Dongsanhuan Beilu,  
 Chaoyang District, 100020 Beijing, P.R.China  
 Telephone: (86)10-6586-6006, Fax: (86)10-6586-2866  
 E-mail: hpc@hamamatsu.com.cn

#### Shanghai Branch

4905 Wheelock Square, 1717 Nanjing Road West,  
 Jingan District, 200040 Shanghai, P.R.China  
 Telephone: (86)21-6089-7018, Fax: (86)21-6089-7017

#### ■ Taiwan:

**HAMAMATSU PHOTONICS TAIWAN Co., Ltd.**  
 Main Office  
 8F-3, No.158, Section2, Gongdao 5th Road,  
 East District, Hsinchu, 300, Taiwan R.O.C.  
 Telephone: (886)3-659-0080, Fax: (886)3-659-0081  
 E-mail: info@hamamatsu.com.tw

#### ■ U.S.A.:

**HAMAMATSU CORPORATION**  
 Main Office  
 360 Foothill Road, Bridgewater, NJ 08807, U.S.A.  
 Telephone: (1)908-231-0960, Fax: (1)908-231-1218  
 E-mail: usa@hamamatsu.com

#### California Office

2875 Moorpark Ave. San Jose, CA 95128, U.S.A.  
 Telephone: (1)408-261-2022, Fax: (1)408-261-2522  
 E-mail: usa@hamamatsu.com

#### Chicago Office

4711 W.Golf Road, Suite 805, Skokie, IL 60076, U.S.A.  
 Telephone: (1)847-825-6046, Fax: (1)847-825-2189  
 E-mail: usa@hamamatsu.com

#### Boston Office

20 Park Plaza, Suite 312, Boston, MA 02116, U.S.A.  
 Telephone: (1)617-536-9900, Fax: (1)617-536-9901  
 E-mail: usa@hamamatsu.com

#### ■ United Kingdom:

**HAMAMATSU PHOTONICS UK Limited**  
 Main Office  
 2 Howard Court, 10 Tewin Road, Welwyn Garden City,  
 Hertfordshire AL7 1BW, UK  
 Telephone: (44)1707-294888, Fax: (44)1707-325777  
 E-mail: info@hamamatsu.co.uk

#### South Africa Contact:

9 Beukes Avenue, Highway Gardens, Edenvale  
 1609 South Africa  
 Telephone/Fax: (27)11-609-0367

#### ■ France, Portugal, Belgium, Switzerland, Spain:

**HAMAMATSU PHOTONICS FRANCE S.A.R.L.**  
 Main Office  
 19, Rue du Saule Trapu, Parc du Moulin de Massy,  
 91882 Massy Cedex, France  
 Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10  
 E-mail: infos@hamamatsu.fr

#### Swiss Office

Dornacherplatz 7, 4500 Solothurn, Switzerland  
 Telephone: (41)32-625-60-60, Fax: (41)32-625-60-61  
 E-mail: swiss@hamamatsu.ch

#### Belgian Office

Axisparc Technology, rue Andre Dumont 7  
 1435 Mont-Saint-Guibert, Belgium  
 Telephone: (32)10 45 63 34, Fax: (32)10 45 63 67  
 E-mail: info@hamamatsu.be

#### Spanish Office

C. Argenters, 4 edif 2 Parque Tecnológico del Vallés  
 08290 Cerdanyola (Barcelona), Spain  
 Telephone: (34)93 582 44 30, Fax: (34)93 582 44 31  
 E-mail: info@hamamatsu.es

#### ■ Germany, Denmark, The Netherlands, Poland:

**HAMAMATSU PHOTONICS DEUTSCHLAND GmbH**  
 Main Office  
 Arzbergerstr. 10, D-82211 Herrsching am Ammersee,  
 Germany  
 Telephone: (49)8152-375-0, Fax: (49)8152-265-8  
 E-mail: info@hamamatsu.de

#### Danish Office

Lautruphøj 1-3, DK-2750 Ballerup, Denmark  
 Telephone: (45)70 20 93 69, Fax: (45)44 20 99 10  
 Email: info@hamamatsu.dk

#### Netherlands Office

Transistorstraat 7, NL-1322 CJ Almere, The Netherlands  
 Telephone: (31)36-5405384, Fax: (31)36-5244948  
 E-mail: info@hamamatsu.nl

#### Poland Office

10 Ciolka Street, RN 126-127 01-402 Warsaw, Poland  
 Telephone: (48)22-646-0016, Fax: (48)22-646-0018  
 E-mail: poland@hamamatsu.de

#### Israel Office (Hamamatsu Photonics Israel Ltd.)

Hahoshlim 6, Building C, 4672201 Herzliya, Israel  
 E-mail: info@hamamatsu.co.il

#### ■ North Europe and CIS:

**HAMAMATSU PHOTONICS NORDEN AB**  
 Main Office  
 Torshamnsgatan 35 16440 Kista, Sweden  
 Telephone: (46)8-509 031 00, Fax: (46)8-509 031 01  
 E-mail: info@hamamatsu.se

#### Russian Office

11, Christophudny Boulevard, Building 1, Office 114,  
 101000, Moscow, Russia  
 Telephone: (7)495 258 85 18, Fax: (7)495 258 85 19  
 E-mail: info@hamamatsu.ru

#### ■ Italy:

**HAMAMATSU PHOTONICS ITALIA S.r.l.**  
 Main Office  
 Strada della Moia, 1 int. 6, 20020 Arese (Milano), Italy  
 Telephone: (39)02-93 58 17 33, Fax: (39)02-93 58 17 41  
 E-mail: info@hamamatsu.it

#### Rome Office

Viale Cesare Pavese, 435, 00144 Roma, Italy  
 Telephone: (39)06-50 51 34 54,  
 E-mail: inforoma@hamamatsu.it

*Information in this catalog is believed to be reliable.  
 However, no responsibility is assumed for possible  
 inaccuracies or omission.  
 Specifications are subject to change without notice.  
 No patent rights are granted to any of the circuits  
 described herein.  
 © 2020 Hamamatsu Photonics K.K.*

Quality, technology and service are part of every product.