


Quantum Cascade Laser (QCL)

Connection example of Quantum cascade laser(QCL)

■ Connection example of DFB-CW QCL

...Our products




■ Recommended instruments

Instruments	Manufacture	Type. No
DC power supply for CW semiconductor laser	Wavelength Electronics Inc.	QCL1500 OEM(+)*1
DC power supply for C11330-01	TDK-Lambda Corporation	HWS100A-24/A
Power cable for C11330-01	Shielded and twisted pair cable: Multi-Conductor 2 (1pair twisted) Ampacity>4.0 A, 150 V	—
DC power supply for A11709-01	General-purpose DC power supply, 12 V/0.47 A	—
USB serial converter	RATOC Systems, Inc.	REX-USB60F

\*1 Designed to be built into equipment

## ■ Connection example of DFB-Pulsed QCL

...Our products



- \*1 The photo is TO-8 pulse driver C14277 mounted a TO-8 packaged QCL.
- \*2 The drive cable should be properly terminated for connecting TEC temperature controller and power supply.
- \*3 This connection example is for C14277-01. Function generator is not required for C14277-02 operation.
- \*4 A couple of A11334-06 is needed each for C14277-01/02 operation.
- \*5 One end of the cable for TEC temperature controller is unterminated and so should be properly terminated by the user.
- \* Products shown in photos are Hamamatsu products. Product names and part numbers are written in red.
- \* Prepare other necessary devices and cables.

## ■ Recommended instruments

Instruments	Manufacture	Type. No
DC power supply for V(ic) input	Keysight Technologies Inc.	E3620A
DC power supply for HV input		—
Dry cable	Shielded and twisted pair cable: Multi-Conductor 8(4 pair twisted), Ampacity>2.2 A, 150 V	—
Coaxial cable	Coaxial cable (50 Ω) SMB-BNC	—
DC power supply for C11330-02	TDK-Lambda Corporation	HWS50A-24/A
Power cable for C11330-02	Shielded and twisted pair cable: Multi-Conductor 2(1 pair twisted), Ampacity>4.0 A, 150 V	—
USB serial converter	RATOC Systems, Inc.	REX-USB60F
Oscilloscope	Oscilloscope with over 300 MHz bandwidth	—

## HAMAMATSU PHOTONICS K.K. [www.hamamatsu.com](http://www.hamamatsu.com)

HAMAMATSU PHOTONICS K.K., Laser Promotion Division, Business Promotion G.  
1-8-3, Shinmiyakoda, Kita-ku, Hamamatsu City, Shizuoka, 431-2103, Japan, Telephone: (81)53-484-1301, Fax: (81)53-484-1302, E-mail: sales-laser@lpd.hpk.co.jp

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, Bridgewater, NJ 08807, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218 E-mail: usa@hamamatsu.com  
Germany: Hamamatsu Photonics Deutschland GmbH.: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-265-8 E-mail: info@hamamatsu.de  
France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10 E-mail: infos@hamamatsu.fr

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, UK, Telephone: (44)1707-294888, Fax: (44)1707-325777 E-mail: info@hamamatsu.co.uk  
North Europe: Hamamatsu Photonics Norden AB: Torshamnsgatan 35 16440 Kista, Sweden, Telephone: (46)8-509 031 00, Fax: (46)8-509 031 01 E-mail: info@hamamatsu.se  
Italy: Hamamatsu Photonics Italia S.r.l.: Strada della Moia, 1 int. 6, 20020 Arese (Milano), Italy, Telephone: (39)02-93 58 17 33, Fax: (39)02-93 58 17 41 E-mail: info@hamamatsu.it  
China: Hamamatsu Photonics (China) Co., Ltd.: 1201 Tower B, Jiaming Center, 27 Dongsanhuan Beilu, Chaoyang District, 100020 Beijing, China, Telephone: (86)10-6586-6006, Fax: (86)10-6586-2866 E-mail: hpc@hamamatsu.com.cn  
Taiwan: Hamamatsu Photonics Taiwan Co., Ltd.: 8F-3, No.158, Section2, Gongdao 5th Road, East District, Hsinchu, 300, Taiwan R.O.C. Telephone: (886)03-659-0080, Fax: (886)03-659-0081 E-mail: info@hamamatsu.com.tw

Cat. No. LQCL3004E01  
NOV. 2019 CRD