

# InAsSb photovoltaic detector arrays



P15742 series

**16, 46 element array capable of detecting up to 5  $\mu\text{m}$  band**

The P15742 series is one-dimensional InAsSb photovoltaic detector array in a ceramic DIP (dual inline package). They have a back-illuminated structure that achieves low crosstalk. These are environmentally friendly infrared detectors that do not use lead, mercury, or cadmium, which are substances restricted by the RoHS Directive.

## Features

- High sensitivity
- Low crosstalk

## Applications

- Infrared spectrophotometry
- Temperature measurement
- Remote sensing

## Structure

Parameter	P15742-016DS	P15742-046DS	Unit
Number of elements	16	46	-
Element size	0.45 × 0.7	0.2 × 0.7	mm
Element pitch	0.5	0.25	mm
Package	18-pin ceramic DIP	48-pin ceramic DIP	-
Window material	Sapphire		-

## Absolute maximum ratings (Ta=25 °C, unless otherwise noted)

Parameter	Symbol	Condition	Value	Unit
Reverse voltage	VR		1	V
Operating temperature	Topr	No dew condensation*1	-20 to +70	°C
Storage temperature	Tstg	No dew condensation*1	-20 to +80	°C

\*1: When there is a temperature difference between a product and the surrounding area in high humidity environments, dew condensation may occur on the product surface. Dew condensation on the product may cause deterioration in characteristics and reliability.


Note: Exceeding the absolute maximum ratings even momentarily may cause a drop in product quality. Always be sure to use the product within the absolute maximum ratings.

## Electrical and optical characteristics (Ta=25 °C, per element)


Parameter	Symbol	Condition	P15742-016DS			P15742-046DS			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	
Peak sensitivity wavelength	$\lambda_p$		-	3.5	-	-	3.5	-	$\mu\text{m}$
Cutoff wavelength	$\lambda_c$		5	5.3	-	5	5.3	-	$\mu\text{m}$
Photosensitivity	S	$\lambda = \lambda_p$	5	6.5	-	11.6	14.6	-	mA/W
Shunt resistance	Rsh	VR=10 mV	70	180	-	24	60	-	k $\Omega$
Detectivity	D*	( $\lambda_p$ , 1200, 1)	$8 \times 10^8$	$1 \times 10^9$	-	$8 \times 10^8$	$1 \times 10^9$	-	cm <sup>2</sup> Hz <sup>1/2</sup> /W
Rise time	tr	VR=0 V, RL=50 $\Omega$ 10 to 90%, $\lambda=1.55 \mu\text{m}$	-	15	-	-	15	-	ns
Terminal capacitance	Ct	VR=0 V, f=1 MHz	-	40	-	-	50	-	pF
Noise equivalent power	NEP	$\lambda = \lambda_p$	-	$5.6 \times 10^{-11}$	$7 \times 10^{-11}$	-	$4.2 \times 10^{-11}$	$5.3 \times 10^{-11}$	W/Hz <sup>1/2</sup>

Note: Uniform irradiation on the entire photosensitive area

**Spectral response**




**Shunt resistance vs. chip temperature**




**Crosstalk characteristics**

P15742-016DS





P15742-046DS



Dimensional outlines (unit: mm)



P15742-016DS



Chip position accuracy with respect to package center  
 $X, Y \leq \pm 0.3, \theta \leq \pm 3^\circ$

KIRDA0270EA


P15742-046DS



Chip position accuracy with respect to package center  
 $X, Y \leq \pm 0.3, \theta \leq \pm 3^\circ$

KIRDA0271EA

▣ Details of photosensitive area (unit: mm)



Number of elements	x	H	V
16	0.45	0.5	0.7
46	0.2	0.25	

KIRDC0131EA

▣ Pin connections

Pin no.	P15742-016DS	P15742-046DS	Pin no.	P15742-016DS	P15742-046DS
1	KC	KC	25		KC
2	2	2	26		45
3	4	4	27		43
4	6	6	28		41
5	8	8	29		39
6	10	10	30		37
7	12	12	31		35
8	14	14	32		33
9	16	16	33		31
10	KC	18	34		29
11	15	20	35		27
12	13	22	36		25
13	11	24	37		23
14	9	26	38		21
15	7	28	39		19
16	5	30	40		17
17	3	32	41		15
18	1	34	42		13
19		36	43		11
20		38	44		9
21		40	45		7
22		42	46		5
23		44	47		3
24		46	48		1

Note: KC: cathode (common), other than cathode: anode

### Recommended soldering conditions

Solder temperature: 260°C (5 s or less, once)

Solder the leads at a point at least 1.5mm away from the package body.

Note: When you set soldering conditions, check that problems do not occur in the product by testing out the conditions in advance.

### Related information

[www.hamamatsu.com/sp/ssd/doc\\_en.html](http://www.hamamatsu.com/sp/ssd/doc_en.html)

#### ■ Precautions

- Disclaimer
- Safety consideration
- Compound opto-semiconductors (photosensors, light emitters)

Information described in this material is current as of January 2021.

Product specifications are subject to change without prior notice due to improvements or other reasons. This document has been carefully prepared and the information contained is believed to be accurate. In rare cases, however, there may be inaccuracies such as text errors. Before using these products, always contact us for the delivery specification sheet to check the latest specifications.

The product warranty is valid for one year after delivery and is limited to product repair or replacement for defects discovered and reported to us within that one year period. However, even if within the warranty period we accept absolutely no liability for any loss caused by natural disasters or improper product use. Copying or reprinting the contents described in this material in whole or in part is prohibited without our prior permission.

# HAMAMATSU

[www.hamamatsu.com](http://www.hamamatsu.com)

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81)53-434-3311, Fax: (81)53-434-5184

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, Bridgewater, N.J. 08807, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218, E-mail: [usa@hamamatsu.com](mailto:usa@hamamatsu.com)

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-265-8, E-mail: [info@hamamatsu.de](mailto:info@hamamatsu.de)

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10, E-mail: [infos@hamamatsu.fr](mailto:infos@hamamatsu.fr)

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, UK, Telephone: (44)1707-294888, Fax: (44)1707-325777, E-mail: [info@hamamatsu.co.uk](mailto:info@hamamatsu.co.uk)

North Europe: Hamamatsu Photonics Norden AB: Torshamnsgatan 35 16440 Kista, Sweden, Telephone: (46)8-509 031 00, Fax: (46)8-509 031 01, E-mail: [info@hamamatsu.se](mailto:info@hamamatsu.se)

Italy: Hamamatsu Photonics Italia S.r.l.: Strada della Moia, 1 int. 6, 20020 Arese (Milano), Italy, Telephone: (39)02-93 58 17 33, Fax: (39)02-93 58 17 41, E-mail: [info@hamamatsu.it](mailto:info@hamamatsu.it)

China: Hamamatsu Photonics (China) Co., Ltd.: 1201 Tower B, Jiaming Center, 27 Dongsanhuan Beilu, Chaoyang District, 100020 Beijing, P.R.China, Telephone: (86)10-6586-6006, Fax: (86)10-6586-2866, E-mail: [hpc@hamamatsu.com.cn](mailto:hpc@hamamatsu.com.cn)

Taiwan: Hamamatsu Photonics Taiwan Co., Ltd.: 8F-3, No. 158, Section2, Gongdao 5th Road, East District, Hsinchu, 300, Taiwan R.O.C. Telephone: (886)3-659-0080, Fax: (886)3-659-0081, E-mail: [info@hamamatsu.com.tw](mailto:info@hamamatsu.com.tw)